



LTB-WR-SRS Headphone (2.4 GHz Digital 5.1 Surround)

The LTB wireless 5.1 six-channels headphone feature everything that modern technology can achieve for wireless headphones. It is a true 5.1 six channel surround sound wireless headphone system. Apart from first-class high-end wireless headphones, digital radio transmission and digital antenna diversity for absolutely noise-free reception without drop-outs, it is also fitted with a Dolby Digital and Dolby Pro Logic decoder. This is the ideal surround system for all Hi-Fi enthusiasts and who want to get optimum acoustic performance from their equipment.

LTB-WR-SRS by far, is the first & the only one, 5.1 surround digital wireless headphone out there. Radio transmission ensures optimal even though walls and ceilings, with a range of up to 100m (under ideal transmission conditions, free-field).

Features-Benefits:

LTB Transmitter

- 2.4 GHz digital radio transmission (absolutely noise-free).
- Coaxial cable or optical fiber input.
- 10 mW transmitting power.
- Four selectable RF channels.

LTB Receiver

- Freedom of surround sound with reception through walls and ceilings, even outside in the garden.
- Digital antenna diversity guarantees drop-out free reception.
- Integrated Dolby Digital and Dolby Pro Logic Decoder.
- CMOS headphone amplifier for superior sound quality.
- Range of up to 100 meters.

LTB Headphone

- Multiple speaker units for front, rear, center and subwoofer channels.
- Performance equality high-end hardwire headphones.
- Very lightweight, extremely comfortable to wear

Specification:

LTB Headphone:

Net Weight (without cord):	170 Grams (6 ounce)
True 5.1 surround sound :	Yes
Independent speaker chambers:	Yes / 6
Drive Unit (speaker size):	
Center:	15 mm X2
Surround:	15 mm X2
Front:	40 mm X2
Max Power:	15 mW
Impedance:	
Center:	16 Ω
Surround:	8 Ω
Front:	32 Ω
Frequency Response:	20Hz - 20 KHz
T.H.D.	< 3%
Cord Length:	7 ft

LTB-WR-ST Transmitter & Receiver:

Net Weight:	
Transmitter:	180 Grams
Receiver:	
Dimensions:	
Transmitter:	78 x23 x118 mm
Receiver:	84 x33 x130 mm
Power:	
Transmitter:	9V DC Adapter
Receiver:	AA batteries
RF frequency range:	2410, 2430, 2450 and 2470MHz
Modulation:	FSK
Power Consumption:	
Transmitter:	Approx 50 mA
Receiver:	Approx 290mA
Operating time (Battery):	Approx 5-6 hrs

Sunnytech Inc.

375 North St. unit #N. Teterboro, NJ 07608 Phone: 201-883-1130 Fax: 201-883-0685

www.listentobelieve.com