



FMS-500

Fleet Management System

Functions as: Incident Data Recorder
Vehicle Fleet Management Device

	Standard	Optional
CAN Bus	●	2x High Speed CAN : up to 1Mbit / s Interfaces J1962 / OBD-2 Connector Supports J1939 or KWP2000 Protocols
Internal Memory	●	2 - 8 Mb E ² PROM
Switch Inputs	●	22 Interruptable Capable Inputs (0-12v) or 0 - 5V Analog Input
Serial Interface	●	2 Serial RS-232
Ride Quality Accelerometer		● +/- 1.7g 2 Axis
Incident Accelerometer		● +/- 50g 2 Axis
Yaw Rate Sensor		●
GPS with External Antenna		● NMEA Output Protocol
Internal GSM		● Tri-Band GSM/GPRS Modem
WLAN with Ethernet		● 802.11b

Additional Features:

- Configurable Event Triggers
- Low Power Sleep Mode
- Wake Up on CAN or Switch Inputs
- 4 High Side Outputs (indicator lamps, etc.)
- 4 Low Side Outputs (relays, etc.)

Contact Information

SI-GATE GMBH ● ROBERT BOSCH STR. 9 ● D-64331 WEITERSTADT ● GERMANY
TEL: ++49 (0) 6151 / 667 0678 ● E-MAIL : INFO@SI-GATE.COM ● WWW.SI-GATE.COM

Disclaimer: Laws vary from country to country concerning the gathering of data. User/customer is responsible for the proper use of this product concerning the region(s) they are in. SI-Gate GmbH shall not be held liable for any improper usage.

Rev. 1.0 August, 2005