

2U rack mount system Front I/O layout 3 x full size PCI expansion slots



» Features

- » 2U rackmount system, 17" depth
- » Intel Pentium D / Core 2 Duo processor
- » Front I/O layout
- » front accessible PCI-32 full-size expansion slots
- » Built-in Audio/Video/LAN
- » Built-in standard 300W PS/2 power supply

» Specifications

Construction:

Heavy-duty cold-rolled steel.
Inside: zinc-plated with bright chromate,
Outside: texture-coated

ATX M/B:

Size: 12" x 9.6" ATX mother board
Processor: Intel Pentium 4/D CPU, 533/800FSB
Memory: support DDR/DDR2 memory (up to 2GB)
On-board Video
On-board Audio
On-board 10/100BT LAN
1 x Serial and 1x parallel ports

Devices:

1 x slim-type 24X CD-ROM
Optional for DVD/DVD RW
2 x 3.5" hidden drive bay (for 3.5" EIDE HD)

Front expansion slot:

3 front accessible PCI-32 full-size (13" depth) expansion slots

Front Panel Connector:

6 x USB ports
1 x VGA port
1 x Audio Line in/out, Mice
1 x RJ-45, 10/100BT LAN port
1 x RS-232 port
1 x parallel port

Front Panel Controls:

Power on/off switch
System reset button

Cooling Fan:

Front:
2 x 40mm ball-bearing fans
Back:
1 x 80mm all-bearing fan

Power supply:

PS/2 type 300W 110/220VAC power supply

Slide rail (optional):

20" slide rail

Color:

Black

Operation Temperature:

0°C (32°F)~40°C (104°F)

Humidity:

5%~95% non-condensing

Gross Weight:

40lb

Dimension:

19"(W) x 17"(D) x 3.5"(H)

» Options

PS-400: 400W ATX power supply

PS-500: 500W ATX power supply

SL20: 20" slide rail

» Ordering Guide

RMC 7217A:

2U rackmount computer with front I/O, 3 PCI-32 full-size expansion slots.