

HauteSpot Networks Manufactuered Products

	PERFORMANCE											
[SPECIALTY PRODUCTS			
	HR-WRAPSX	HR.WRAPSYI	HR.WRAPDX	HR.WRAPDXI	HR-IXPSXP (HR-IXPBXP Gov and export)	HR-IXPSXPs	HR-IXPDX	HR-IXPSXPi	HR-IXPSXPI-SD (HR-IXPBXPI-SD Gov and export)	HR-IXPSX-WIND	HR-MobiTow	
									L	3-67	1	
Description	Highly configurable, single radio Outdoor router with moderate performance	Highly configurable, single radio Indoor router with moderate performance	Highly configurable, dual radio Outdoor router with moderate performance	Highly configurable, dual radio Indoor router with moderate performance	High performance single radio Outdoor streaming media wireless bridge	High performance single radio Outdoor streaming media wireless bridge with Serial Over IP and Antenna Diversity	High performance general purpose dual radio Outdoor wireless router, repeater, base station, bridge	High performance single radio Indoor streaming media wireless bridge	High performance Indoor streaming media wireless bridge with integrated MPEG2 SD encoder and streaming server	Wireless Outdoor weather station for long range applications	Free standing portable 24" tall mobile tower	
Throughput		24 Mbps TCP/IP	24 Mbps TCP/IP	24 Mbps TCP/IP	65 Mbps TCP/IP	65 Mbps TCP/IP	200Mbps TCP/IP aggregate	65 Mbps TCP/IP	65 Mbps TCP/IP	36 Mbps TCP/IP		
Applications	Moderate Density and Performance Access Point, Singleband Repeater, P2P Bridge, WIDS Mesh Node, Client Bridge, Wireless Router, Host Controller, Interoperates with any 802.11 equipment.	Moderate Density and Performance Access Point, Singleband Repeater, P2P Bridge, WDS Mesh Node, Client Bridge, Wireless Router, host Controller, Interoperates with any 802.11 equipment.	Moderate Density and Performance Access Point, Multiband Repeater, P2P Bridge, WDS Mesh Node, Client Bridge, Wireless Router, Host Controller, Interoperates with any 802.11 equipment.	Moderate Density and Performance Access Point, Multiband Repeater, P2P Bridge, WIDS Mesh Node, Client Bridge, Wireless Router, Host Controller, Interoperates with any 802.11 equipment.	High Performance P2P Streaming Media Bridge for Ho To SU dae or high capacity voice over IP. Use with external encoders or VeIP switchesigherways. Ideal for SCADA applications where low latency is required. Order in pairs or use as base station to HR- DOPSXPI-SD	High Performance P2P Steaming Media Bridge for Ho o SD Video or high capacity voice over IP. Use with external encoders or VipIP witchesigherways. Ideal for SCADA applications. Diversity aids mobile applications or links that are partially obstructed. Serial over IP support for remote control applications. Order in pairs or use as base station to HR-IXPSXPI-SD	High Donsity and Performance Access Point, Multiband Repeater, P29 Bridge, WDS Mesh Node, Client Bridge, Werless Router. Interoperates with any 802.11 equipment or HauteLine equipment. Make transitions between HauteLine backhaul and 802.11 distribution/access.	High Performance P2P Streaming Media Bridge for HID < 50 Video or high capacity voice over IP. Use with external encoders or VeriP switches/gateways. Ideal for SCADA applications where low latency is required. Setal over IP support for remote control applications. Order in pairs or use as base station to HR-00PSXPI-SD	encoder, and multicast streaming engine. Can be used with external encoder as well.	Long Range, Wireless Weather Station with optional integrated camera. Manitors temp, humidity, barometric pressure, wind speed and direction. Compabile with WeatherUnderground. Fully self contained. Use with HR-D9SY base station. Can run from batteries, solar or other power sources		
Enclosure Options	NEMA 4 IP6/7 waterproof outdoor	lightweight extruded aluminum case for indoors or in vehicles	NEMA 4 IP6/7 waterproof outdoor	lightweight extruded aluminum case for indoors or in vehicles	NEMA 4 IP6/7 waterproof outdoor	NEMA 4 IP6/7 waterproof outdoor	NEMA 4 IP6/7 waterproof outdoor	Lightweight blue sheet metal enclosure. Small enough for camera back or vechile mounting. Can be belt worn too.	Lightweight black extruded aluminum enclosure. Small enough for camera back or wechile mounting. Can be belt worn too.	NEMA 4 IP6/7 waterproof outdoor		
Wireless	1	1	2	2	1	1	2	1	1	1		
Frequencies Supported	900MHz 2.3.2.5GHz (ISM 2.4GHz, others Gov and export only) 4.9GHz (FCC Part 90Y Public Safety only) 5.0.6.1GHz (NII 5.1-58GHz, others Gov and export only)	900MHz 2.3-z.5GHz (ISM 2.4GHz, others Gov and export only) 4.9GHz (FCC Part 90Y Public Safety only) 5.0-6.1GHz (NII 5.1-5.8GHz, others Gov and export only)	900MHz 2.3.2.5GHz (ISM 2.4GHz, others Gov and export only) 4.9GHz (PCC Part 90Y Public Safety only) 5.0-6.1GHz (NII 5.1-5.8GHz, others Gov and export only)	900MHz 2.3.2.5GHz (ISM 2.4GHz, others Gov and export only) 4.9GHz (FCC Part 90Y Public Safety only) 5.0-6.1GHz (NII 5.1-5.9GHz, others Gov and export only)	900MHz 1.6GHz (Gov and export only) 2.2-2.5GHz (BM 2.4GHz, others Gov and export only) 4.4GHz (Gov and export only) 4.5GHz (FCC Part 90'V Public Safety only) 5.0-6.1GHz (MI 6.1-5.6GHz, others Gov and export only)	900MHz 1.8GHz (Gov and export only) 2.32.5GHz (BM 2.4GHz, others Gov and export only) 4.4GHz (Gov and export only) 4.4GHz (FCC Part 90'V Public Safety only) 5.0-6.1GHz (MIS.1-5.8GHz, others Gov and export only)	900Metz 2-3-2 SGHz (ISM 2-4GHz, others Gov and export only) 4-SGHz (FCC Part 90Y Public Safety only) 5-6-6-1GHz (NII 5.1-5-8GHz, others Gov and export only)		900Metz 1.9Gbt (Gov and export only) 2.2-2.5Gbt (BM 2.4Gbtz, others Gov and export only) 4.4Gbtz (Gov and export only) 4.4Gbtz (Gov and export only) 4.9Gbtz (FCC Part 90'V Public Safety only) 5.0-6.1Gbtz (Mil 6.1-5.8Gbtz, others Gov and export only)	900MHz 2.3-2.5GHz (ISM 2.4GHz, others Gov and export only) 4.9GHz (PCC Part 90Y Public Safety only) 5.0-6.1GHz (NII 5.1-5.8GHz, others Gov and export only)		
Channel Width	5,10,20,40MHz DSSS, OFDM	5,10,20,40MHz DSSS, OFDM	5,10,20,40MHz DSSS, OFDM	5,10,20,40MHz DSSS, OFDM	5,10,20,40MHz OFDM	5,10,20,40MHz	5,10,20,40MHz DSSS, OFDM	5,10,20,40MHz OFDM	5,10,20,40MHz OFDM	5,10,20,40MHz		
Wireless	802.11a,b,d,e,f,g,h,i	802.11a,b,d,e,f,g,h,i	802.11a,b,d,e,f,g,h,i	802.11a,b,d,e,f,g,h,i	OFDM HauteLine Streaming Media	HauteLine Streaming Media	802.11a,b,d,e,f,g,h,I	HauteLine Streaming Media	OFDM HauteLine Streaming Media	HauteLine Streaming Media		
Protocols Supported	Proprietary bonding	Proprietary bonding	Proprietary bonding	Proprietary bonding			HauteLine Streaming Media					
Transmit Gain	900MHz 700mW (28dBm) 2.3-2.5GHz 400mW (28dBm) 4.9GHz 400mW (28dBm) 5.1-6.1GHz 400mW (28dBm)	900MHz 700mW (28dBm) 2.3-2.5GHz 400mW (28dBm) 4.9GHz 400mW (28dBm) 5.1-6.1GHz 400mW (28dBm)	900MHz 700mW (28dBm) 2.3-2.5GHz 400mW (26dBm) 4.9GHz 400mW (26dBm) 5.1-6.1GHz 400mW (26dBm)	900MHz 700mW (28dBm) 2.3-2.5GHz 400mW (28dBm) 4.9GHz 400mW (28dBm) 5.1-6.1GHz 400mW (28dBm)	4.9GHz 400mW (26dBm) 5.1-6.1GHz 400mW (26dBm)	900MHz 700mW (28dBm) 1.8GHz 500mW (27dBm) 4.4GHz 500mW (27dBm) 2.3-2.5GHz 400mW (28dBm) 4.9GHz 400mW (28dBm) 5.1-6.1GHz 400mW (28dBm)	900MHz 700mW (28dBm) 1.8GHz 500mW (27dBm) 4.4GHz 500mW (27dBm) 2.3-2.5GHz 400mW (28dBm) 4.9GHz 400mW (28dBm) 5.1-6.1GHz 400mW (28dBm)	900MHz 700mW (28dBm) 1.8GHz 500mW (27dBm) 4.4GHz 500mW (27dBm) 2.3-2.5GHz 400mW (28dBm) 4.9GHz 400mW (28dBm) 5.1-6.1GHz 400mW (28dBm)	900MHz 700mW (28dBm) 1.8GHz 500mW (27dBm) 4.4GHz 500mW (27dBm) 2.3-2.5GHz 400mW (28dBm) 4.9GHz 400mW (28dBm) 5.1-6.1GHz 400mW (28dBm)	900MHz 700mW (28dBm) 1.8GHz 500mW (27dBm) 4.4GHz 500mW (27dBm) 2.3-2.5GHz 400mW (28dBm) 4.9GHz 400mW (28dBm) 5.1-6.1GHz 400mW (28dBm)		
Receive Sensitivity	900MHz -93dBm 2.3-2.5GHz -96dBm	900MHz -93dBm 2.3-2.5GHz -96dBm	900MHz -93dBm 2.3-2.5GHz -96dBm	900MHz -93dBm 2.3-2.5GHz -96dBm	900MHz -93dBm 1.8GHz -108dBm	900MHz -93dBm 1.8GHz -108dBm	900MHz -93dBm 1.8GHz -108dBm	900MHz -93dBm 1.8GHz -108dBm	900MHz -93dBm 1.8GHz -108dBm	900MHz -93dBm 1.8GHz -108dBm		
,	4.9GHz -94dBm 5.1-6.1GHz -94dBm	4.9GHz -94dBm 5.1-6.1GHz -94dBm	4.9GHz -94dBm 5.1-6.1GHz -94dBm	4.9GHz -94dBm 5.1-6.1GHz -94dBm	4.4GHz -108dBm 2.3-2.5GHz -98dBm 4.9GHz -94dBm 5.1-6.1GHz -94dBm	4.4GHz -108dBm 2.3-2.5GHz -98dBm 4.9GHz -94dBm 5.1-6.1GHz -94dBm	4.4GHz -108dBm 2.3-2.6GHz -96dBm 4.9GHz -94dBm 5.1-6.1GHz -94dBm	4.4GHz -108dBm 2.3-2.5GHz -98dBm 4.9GHz -94dBm 5.1-6.1GHz -94dBm	4.4GHz -108dBm 2.3-2.6GHz -96dBm 4.9GHz -94dBm 5.1-6.1GHz -94dBm	4.4GHz -108dBm 2.3-2.5GHz -96dBm 4.9GHz -94dBm 5.1-6.1GHz -94dBm		
Processor	AMD Geode LX700	AMD Geode LX700	AMD Geode LX700	AMD Geode LX700	Intel Xscale IXP 420 multicore network processor	Intel Xscale IXP 420 multicore network processor	Intel Xscale IXP 425 multicore network processor with cryptographic hardware acelleration	Intel Xscale IXP 420 multicore network processor	Intel Xscale IXP 420 multicore network processor	Intel Xscale IXP 420		
Memory Storage	128MB SDRAM Removable, low cost CompactFlash	128MB SDRAM Removable, low cost CompactFlash	128MB SDRAM Removable, low cost CompactFlash	128MB SDRAM Removable, low cost CompactFlash	64MB SDRAM High Performance, secure, on-board	64MB SDRAM High Performance, secure, on-board	64MB SDRAM High Performance, secure, on-board	64MB SDRAM High Performance, secure, on-board	64MB SDRAM High Performance, secure, on-board	64MB SDRAM High Performance, secure, on-board		
Operating System	HauteRouterOS - High function, non customizable	HauteRouterOS - High function, non customizable	HauteRouterOS - High function, non customizable	HauteRouterOS - High function, non customizable	StrataFlash HauteRouteOS - Embedded OS optimized for wireless networking. Highly customizable.	StrataFlash HauteRouteOS - Embedded OS optimized for wireless networking. Highly customizable.	StrataFlash HauteRouteOS - Embedded OS optimized for wireless networking. Highly customizable.	StrataFlash HauteRouteOS - Embedded OS optimized for wireless networking. Highly customizable.	StrataFlash HauteRouteOS - Embedded OS optimized for wireless networking. Highly customizable.	StrataFlash HauteRouteOS - Embedded OS optimized for wireless networking. Highly customizable.		
Other	1 week APO	1 week AGO	Superior Addition	1 week ARO	Includes Palauk En erkeaming media protocol which eliminates jitter and delay variation.	includes lyaductine steaming media protocol which eliminates jitter and delay variation.	Includes Hawkine streaming media protocol which eliminates jitter and delay variation.	Includes Hantel me streaming media protocol which eliminates jiter and debay variation.	Includes Hankbline streaming media protocol which eliminate little and delay variation. 100 July 200	The integrated Wind Direction and Speed Sensor, Barcenteir-Inseaure Sensor, Temperature and Humidity Sensor are all readdate from within the web interface, actually the sensor and the sensor are portional. For amore is also available through the Web Interface, Readings can also be superimposed onto streaming mages. Additional sensors for bittery life, solar addition, self modelume, oppourn soil sensor and others are available for custom strengths.	The towers setemt out to 24 and allow for the rapid attachment of any Hautsbegot Networks werdeas router including the HIS WorkPard HI WOOL Genes and matching administration towers will be administration tower so under the submitted and maximum locar is one of the tallect and most rugged artimum locar is one of the tallect and most rugged artimum locar is 20 lbs. At its support a maximum locar of 22 lbs. At lot summarms height, at will support all card of 16 lbs without distinction brancing or sandbagg Orginan should amadiage, wheels, batter systems, wind brancing plyy repres. 10 weeks ARD	
Availability Warranty	1 year Parts and Labor	1 year Parts and Labor	1 year Parts and Labor	1 year Parts and Labor	1 year Parts and Labor	1 year Parts and Labor	1 year Parts and Labor	1 year Parts and Labor	1 year Parts and Labor	1 year Parts and Labor	90 days Parts and Labor	
Antenna Options	Call	Call	Call	Call	Call	Call	Call	Call	Call	Call		
MSRP	\$679 outdoor base price	\$499 indoor base price	\$899 outdoor base price	\$649 indoor base price	Call	Call	Call	Call	Call	Call	Call	



Wireless Broadband Solutions

EnGenius Technologies Manufactuered Products

	STANDARD PRODUCTS Engenius Technologies Manutactuered Products STANDARD PRODUCTS							
	ECB-3220	ECB-8610	EOC-3220	EOC-3220 Plus	EOC-3220 EXT	EOC-8610		
				B	1	1		
Description	802.11b/g Low cost indoor high power, value based access point/client bridge	802.11a/b/g Low cost indoor high power, value based access point/client bridge	802.11b/g Low cost Outdoor high power, value based access point/client bridge with integrated 9dBi panel antenna	802.11b/g Low cost Outdoor high power, value based access point/client bridge with integrated 16dBi panel antenna	802.11b/g Low cost Outdoor high power, value based access point/client bridge with removable omni directional antenna	802.11a/b/g Low cost Outdoor high power, value based access point/client bridge with removable omni directional antenna		
Throughput	15 Mbps TCP/IP	15 Mbps TCP/IP	15 Mbps TCP/IP	15 Mbps TCP/IP	15 Mbps TCP/IP	15 Mbps TCP/IP		
	Value Priced Access Point, Client Bridge. 802.11b/g operation. High transmit power, high receive sensitivity, Ideal for hotels, motels, offices, or high end homes.	Value Priced Access Point, Client Bridge. 802.11a/big operation. High transmit power, high receive sensitivity. Ideal for hotels, motels, offices, or high end homes.	Value Priced Outdoor Access Point, Client Bridge. 802.11bg operation. High transmit power, high receive sensitivity. Ideal for hotels, motels, offices, or high end homes. This model is ideal as remote bridge for client use. Use with EOC-3220 EXT or HR-WRAP as a base station.	Value Priced Outdoor Access Point, Client Bridge. 802.11b/g operation. High transmit power, high receive sensitivity. Ideal for hotels, motels, offices, or high end homes. This model is ideal as remote bridge for client use. Use with EOC-3220 EXT or HR-WRAP as a base station.	Value Priced Outdoor Access Point, Client Bridge, 802.11b/g operation. High transmit power, high receive sensitivity, Ideal for hotels, motels, offices, or high end homes. This model is ideal as a low cost outdoor access point.	Value Priced Outdoor Access Point, Client Bridge, 802.11a/b/g operation. High transmit power, high receive sensitivity. Ideal for hotels, motels, offices, or high end homes. This model is ideal as a low cost outdoor access point.		
Enclosure Options	Plastic indoor	Plastic indoor	UV resistant PVC plastic enclosure. Weather resistant.	UV resistant PVC plastic enclosure. Weather resistant.	UV resistant PVC plastic enclosure. Weather resistant.	UV resistant PVC plastic enclosure. Weather resistant.		
Wireless Interfaces	1	1	1	1	1	1		
Frequencies Supported	2.4GHz	2.4GHz	2.4GHz	2.4GHz	2.4GHz	2.4GHz		
Channel Width	20 MHz	20 MHz	20 MHz	20 MHz	20 MHz	20 MHz		
Modulation	DSSS, OFDM		DSSS, OFDM	DSSS, OFDM	DSSS, OFDM	OFDM		
Wireless Protocols Supported	802.11b,d,e,f,g,h,i	802.11a,b,d,e,f,g,h,i	802.11b,d,e,f,g,h,i	802.11b,d,e,f,g,h,i	802.11b,d,e,f,g,h,i	802.11a,b,d,e,f,g,h,i		
Transmit Gain	400mW (26dBm)	2.4GHz 400mW (26dBm) 5GHz 125mW (20dBm)	400mW (26dBm)	400mW (26dBm)	400mW (26dBm)	2.4GHz 400mW (26dBm) 5GHz 125mW (20dBm)		
Receive Sensitivity	Up to -94dBm	2.4GHz Up to -91dBm 5GHz Up to -88dBm	Up to -94dBm	Up to -94dBm	Up to -94dBm	2.4GHz Up to -91dBm 5GHz Up to -88dBm		
Processor	Realtek 8186	Ubicom/Atheros	Realtek 8186	Realtek 8186	Realtek 8186	Ubicom/Atheros		
Memory	8MB SDRAM	8MB SDRAM	8MB SDRAM	8MB SDRAM	8MB SDRAM	8MB SDRAM		
Storage Operating System	4MB NAND, not removable Proprietary	4MB NAND, not removable Proprietary	4MB NAND, not removable Proprietary	4MB NAND, not removable Proprietary	4MB NAND, not removable Proprietary	4MB NAND, not removable Proprietary		
Other								
Availability	Immediate	Immediate	Immediate	Immediate	Immediate	Immediate		
Warranty	1 year through EnGenius	1 year through EnGenius	1 year through EnGenius	1 year through EnGenius	1 year through EnGenius	1 year through EnGenius		
	Any RPTNC type antenna	Any RPTNC type antenna	Antenna integrated	Antenna integrated	Any RPSMA type	Any RPSMA type		
MSRP	\$129	\$210	\$150	\$160	\$150	\$229		