## **TPC**Flat Festoon Cable

600 Volt • Oil and Sunlight Resistant • 105°C Rated



TPC's Flat Festoon Cable has been specifically designed for use in festoon systems for power and control on cranes and hoists. Cables can also be used where space is at a premium or where extreme flexing is a requirement, recommended bend radius of three to five times cable diameter. TPC's Flat Festoon Cables are suitable for either indoor or outdoor applications operating at -40° C to 105° C.

## FEATURES

- Designed for continuous flexing applications
- Oil and chemical resistant
- Indoor and outdoor rated
- Color coded per ICEA method 1
- Yellow jacketed

## APPLICATIONS

- Festooning Systems
- Cranes
- Telescoping Jetways

- Robots Conveyors
- Hoists
- Track Systems

ORDERING INFORMATION					
PART NO.	SIZE AWG/COND.	BUNCH Stranding	VOLTS	CABLE DIM. THICKNESS x WIDTH (IN.)	WT. (LBS.) PER 1000'
61918	16/8c	65/34	600	.20 x 1.110	192
61912	16/12c	65/34	600	.20 x 1.605	286
61944	14/4c	41/30	600	.217 x .730	142
61948	14/8c	41/30	600	.217 x 1.22	252
61942	14/12c	41/30	600	.217 x 1.81	375
61924	12/4c	65/30	600	.236 x .71	174
61928	12/8c	65/30	600	.236 x 1.650	383
61904	10/4c	105/30	600	.276 x .820	254
61984	8/4c	168/30	600	.36 x 1.15	438
61964	6/4c	266/30	600	.43 x 1.45	679
61994	4/4c	420/30	600	.49 x 1.67	959
61954	2/4c	665/30	600	.56 x 1.97	1416



7061 E. PLEASANT VALLEY RD. INDEPENDENCE, OHIO 44131

800-521-7935 FAX 216-525-4392 CANADA 800-545-0122 MEXICO 800-290-5614 www.tpcwire.com

WARRANTY AND DISCLAIMER: Seller makes no warranties, express or implied, with respect to this product, and seller disclaims any implied warranties of merchantability or fitness for any particular purpose. Further, seller will not be responsible for any consequential, incidental or indirect damages (including, but not limited to, any loss of profit) from any cause whatsoever.