



TPC WIRE & CABLE

A Premier Farnell Company

# Vulko-Wrap™

Self-vulcanizing  
**Insulating Wrap**

- ◀ High dielectric strength; 275/300 volts/mil
- ◀ Wide temperature range; -60° to 400°F
- ◀ High tensile strength; 700 psi min
- ◀ Resistant to oil, water, ozone & many chemicals
- ◀ Meets MIL-I-46852, superseded by CID A-A-59163
- ◀ Adheres only to itself, easy to remove – no adhesive

PART NO.	NOM. THICKNESS	WIDTH x LGTH.	COLOR	DIELECTRIC STRENGTH
<b>98412</b>	<b>40 Mil</b>	1 in. (2.54cm) x 36 ft. (1100cm)	Yellow	300 Volts/Mil
<b>98512</b>	<b>50 Mil</b>	1.5 in. (3.81cm) x 36 ft. (1100cm)	Yellow	275 Volts/Mil
<b>98412BK</b>	<b>40 Mil</b>	1 in. (2.54cm) x 36 ft. (1100cm)	Black	300 Volts/Mil
<b>98512BK</b>	<b>50 Mil</b>	1.5 in. (3.81cm) x 36 ft. (1100cm)	Black	275 Volts/Mil
<b>18412 Reinforced</b>	<b>40 Mil</b>	1 in. (2.54cm) x 36 ft. (1100cm)	Black	500 Volts/Mil

## Economical . . . and easy to use

Vulko-Wrap has no adhesives . . . it only sticks to itself. Cut short, easy to wrap pieces. Keep in mind that Vulko-Wrap may stretch 2 to 3 times its length during application.

- 1** Cut off the desired length.
- 2** Peel off and discard the transparent backing.
- 3** Hold end of Vulko-Wrap over the termination while wrapping the other end around (gently stretching it) until it lays over itself.
- 4** Repeat steps 1, 2 and 3 until the termination is completely encapsulated.

WARRANTY AND DISCLAIMER: Seller makes no warranties, express or implied, with respect to this product, and seller disclaims any implied warranties of merchantability or fitness for any particular purpose. Further, seller will not be responsible for any consequential, incidental or indirect damages (including, but not limited to, any loss of profit) from any cause whatsoever.

TPC157 (REV. 5/08) PRINTED IN U.S.A.  
All rights reserved. No portion of this publication, whether in whole or in part, can be reproduced without the express written consent of Premier Farnell, LLC. ©Copyright 2008 by Premier Farnell, LLC  
®Registered Trademark of Premier Farnell, LLC  
™Trademark of Premier Farnell, LLC

### CONTACT INFORMATION

PHONE **800-521-7935**

CANADA **800-545-0122**

MEXICO **001-800-290-5614**

FAX **216-525-4392**

[www.tpcwire.com](http://www.tpcwire.com)



**Schedule**  
Contract GS-35F-0273P