Material Safety Data Sheet





SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Product Name: Paratherm AC Heat Transfer System Cleaner

Company Identification: Paratherm Corporation

4 Portland Road

West Conshohocken, PA 19428 USA

Product Information: 1-610-941-4900

info@paratherm.com

 Emergency Telephone:
 1-610-941-4900

 Chemtrec (USA):
 1-800-424-9300

 Chemtrec (outside USA):
 1-703-527-3887

SECTION 2 HAZARDS IDENTIFICATION

Emergency Overview

Dark brown liquid with petroleum odor Combustible liquid.

Potential Health Effects:

Eye: Unused product may cause minor eye irritation. Used product will cause irritation .

Skin: Repeated or prolonged contact of new or used product will cause minor skin irritation.

Ingestion: May cause nausea and abdominal discomfort.

Inhalation: Exposure to smoke or mist while product is in use may cause irritation, dizziness and

headaches.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENTS	CAS NUMBER	AMOUNT
Alkylated Aromatic	68855-24-3	40 to 75%
Proprietary Hydrocarbon	Trade Secret	60 to 25%

SECTION 4 FIRST AID MEASURES

Eye: Remove contact lenses if worn. Immediately flush eyes with water for 15 minutes. If symptoms persist, seek medical attention. If fluid is hot, treat burns and seek medical assistance.

Skin: Remove contaminated clothing. Wash exposed areas with warm water and soap. If fluid is hot, submerge injured area in cold water. Seek medical attention for severe burns or if irritation persists.

Ingestion: Seek medical attention. Do not induce vomiting unless instructed by physician.

Inhalation: Remove victim from exposure. If breathing has stopped or is irregular, administer artificial respiration and supply oxygen if available. Seek medical attention.

SECTION 5 FIRE FIGHTING MEASURES

Extinguishing Media: Water fog, foam, dry chemical, or carbon dioxide (CO₂) should be used. Do not use direct water stream

Fire Fighting Instructions: Do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment (including drums) exposed to fire with water if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

Combustion Products: Airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds. May also form various sulfur oxides

SECTION 6 ACCIDENTAL RELEASE MEASURES

Protective Measures: Use personal protection recommended in Section 8.

Spill Management: Ventilate area. Contain release to prevent further contamination of soil, surface water or groundwater. Use appropriate techniques such as non-combustible absorbent materials. Store collected material in a suitable, labeled container. Dispose of contaminated materials in a manner consistent with applicable regulations. If heated material is spilled, allow it to cool to ambient before proceeding with disposal methods. Keep area around hot, spilled material well ventilated.

Reporting: Report spills to appropriate local authorities.

SECTION 7 HANDLING AND STORAGE

Precautionary Measures: Product is not hazardous. Use good personal hygiene practices.

Storage: Store closed containers away from heat, sparks, open flames, or oxidizing materials. Do not transfer to unmarked containers. Protect metal drums from direct sunlight and water.

2 of 4

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Use only in a well-ventilated area

Personal Protective Equipment:

Eye/Face Protection: Safety glasses, chemical type goggles or face shield recommended. .

Skin Protection: Use synthetic rubber (nitrile) protective covers (boots, aprons, gloves) during handling. If material will be handled while hot, wear insulated clothing. Use good personal hygiene practices before and after fluid handling.

Respiratory Protection: No respiratory protection is normally required. If a mist or smoke is generated during use, wear a NIOSH certified organic vapor respirator with a dust and mist filter.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Dark brown liquid **Vapor Pressure:** <1mm @70F (21.1°C)

Odor: Mild chemical odor

pH: NA

Vapor Density (Air = 1): >1

Evaporation Rate (BuAc = 1): <1

 Density: 7.7 lb/gal @ 75 °F (23.9 °C)
 Boiling Point: >500°F (260°C)

 Flashpoint: > 325°F (176.7°C)
 Cleveland
 Solubility: Insoluble in water.

Open Cup Freezing Point: N/A

SECTION 10 STABILITY AND REACTIVITY

Chemical Stability: Stable under normal storage and handling conditions.

Conditions to Avoid: None

Incompatibility With Other Materials: May react with strong oxidizing agents.

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition Products: None known.

SECTION 11 TOXICOLOGICAL INFORMATION

Carcinogenicity:

NTP: No IARC: No OSHA: No

SECTION 12 ECOLOGICAL INFORMATION

Environmental Toxicity: Product is insoluble in water. Keep form entering sewers or surface water.

Biodegradability: Product is not expected to be biodegradable

SECTION 13 DISPOSAL CONSIDERATIONS

Unused material does not meet the criteria of a hazardous waste and can be either recycled or disposed of as synthetic oil. Used product may be classified as a hazardous waste due to byproducts of degradation that could include various aromatic compounds. Used material should be analyzed before disposal.

Revision Number: New 3 of 4 Paratherm AC

SECTION 14 TRANSPORT INFORMATION

US DOT: Not regulated **IATA & IMDG:** Not regulated

SECTION 15 REGULATORY INFORMATION

United States

RCRA Hazardous Waste Number and Classification: Not applicable for unused product

TSCA Inventory Status: Included

SARA Title III Section 313 and 40 CFR 372: Not subject to reporting requirements

SARA 311/312 Categories: Not subject to reporting requirements

California Proposition 65: This product does not contain materials which the state of California

has found to cause cancer, birth defects, or other reproductive harm.

Canada

Domestic Substances List: Listed **WHMIS Classification:** Not controlled

International Inventories:

Australia (AICS) Japan (ENCS)

Europe (EINECS)

EU Risk and Safety Phrases

R53: May cause long-term adverse effects in the aquatic environment

S56: Dispose of this material and it's container at hazardous or special waste collection point

S57: Use appropriate container to avoid environmental contamination.

SECTION 16 OTHER INFORMATION

Recommended Use: Cleaner for liquid phase heat transfer systems

Date of Revision: 9/1/09

Reason for Revision: New

NFPA RATINGS: Health: 1 Flammability: 1 Reactivity: 0

0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

Abbreviations that may have been used in this document

TLV - Threshold Limit Value TWA - Time Weighted Average
STEL - Short-term Exposure Limit PEL - Permissible Exposure Limit

IDLH - Immediate Danger to Life and Health CAS - Chemical Abstract Service Number

NOHSC - Nat'l Occup. Health & Safety Comm. OSHA - Occupational Safety and Health Administration

< - Less Than > - Greater Than

- Less Than or Equal To >= - Greater Than or Equal To

Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and the ANSI MSDS Standard Z400.1).

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

Revision Number: New 4 of 4 Paratherm AC Revision Date: 9/1/09