

GARLOCK KLOZURE® HIGH-PERFORMANCE DYNAMIC SEALS

MICRO-TEC® II Bearing Isolator

Metallic Bearing Isolator with Micro-Cellular Filter

The Metallic Isolator with a built-in air filter...

- ▶ Microcellular filter to block out airborne contamination
- ▶ Unitizing element ensures no internal metal-to-metal contact
- ▶ No internal o-rings
- ▶ No wear on shaft or metallic components
- ▶ Cam-Lock design means easy installation — No tools required
- ▶ One piece unitized design
- ▶ Meets NEMA MG 1-2003
- ▶ Surpasses IEEE 841-2001 Test Standards
- ▶ API Compliant



Microcellular Filter



Design Parameters

- ▶ Temperature: -30°F (-34°C) to 400°F (204°C)
- ▶ Shaft-to-bore misalignment to ± 0.020 " (0.51mm)
- ▶ Axial motion to ± 0.025 " (0.64mm)
- ▶ Surface speed to 4,500 fpm (22.9 m/s)
- ▶ Fluoroelastomer mounted o-rings standard

www.microtec2.com

Garlock Klozure®
HIGH-PERFORMANCE DYNAMIC SEALS

an EnPro Industries company

GARLOCK KLOZURE® HIGH-PERFORMANCE DYNAMIC SEALS

Microcellular Filter

Only the MICRO-TEC® II incorporates a unique microcellular filter to block the ingress of outside contaminants. Bearing isolators with conventional labyrinth seal designs provide only limited airborne contaminant protection.

Patented Unitizing Ring

Unlike other isolators that use a simple o-ring, our patented unitizing ring completely eliminates metal-to-metal contact between the rotor and stator. Lack of axial protection can allow the bronze components to contact. Rotation and misalignment cause abrasion and shredding of the internal o-ring, leading to debris and failure.

Patented Cam-lock Design

The patented Cam-lock design of the MICRO-TEC® II gives it double the retaining power versus standard bearing isolator designs. This design also allows easy installation by hand, without the need for an arbor press. The interference fit of other designs require special tools for installation and may generate bronze shavings that result in bore scoring.

* Patent Pending

AUTHORIZED DISTRIBUTOR**WARNING:**

Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Garlock. Failure to select the proper sealing products could result in property damage and/or serious personal injury.

Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing.

While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice.

GARLOCK is a registered trademark for packings, seals, gaskets, and other products of Garlock.

© Garlock Inc 2007. All rights reserved worldwide.

Garlock Klokure®

A Division of Garlock Sealing Technologies®

1666 Division Street

Palmyra, New York 14522 USA

1.315.597.4811

Fax 1.315.597.3140

Toll Free 1.866.KLOZURE (1.866.556.9873)

Toll Free Fax: 1.866.OILSEAL (1.866.645.7325)

Visit Klokure:

www.klokure.com

www.microtec2.com

Other Garlock brand facilities are located in:

Columbia, SC, USA

1-803-783-1880

Fax: 1-803-783-4279

Houston, TX, USA

1-281-459-7200

Fax: 1-281-458-0502

Sydney, Australia

61-2-9793-2511

Fax: 61-2-9793-2544

São Paulo, Brazil

55-11-4352-6161

Fax: 55-11-4352-8181

Sherbrooke, Canada

1-819-563-8080

Fax: 1-819-563-5620

West Yorkshire, England

44-1422-313600

Fax: 44-1422-313601

Saint-Étienne, France

33-4-7743-5100

Fax: 33-4-7743-5151

Neuss, Germany

49-2131-3490

Fax: 49-2131-349-222

Mexico City, Mexico

52-555-567-7011

Fax: 52-555-368-0418

Shanghai, China

86-021-62789702

Fax: 86-021-62787826

Singapore

65-6285-9322

Fax: 65-6284-5843

Dubai, UAE

971-4-8833652

Fax: 971-4-8833682

PRINTED IN U.S.A.

KLZ 2:78

VIA-10/05



Garlock Sealing Technologies® is
an EnPro Industries company.

Bring Garlock Klokure® to all your sealing requirements

