

2010 IEEE Reliability

How Carbon Footprints, Green Initiatives and Reliability Work Together or Against Each Other









It's an increasingly polluted world out there

- 27% of all deaths in China are now lung related (2007)
- If it is impacting tissue, what is it doing to metal objects, electronics, telecomm equipment?

Environmental Legislation and miniaturization makes electronics potentially more at risk for damage

Reliability Through Packaging



Some Sobering Statistics

Although for the most part, the plant-floor metrics of facilities in the "2007 China Manufacturing Study" (conducted by the Manufacturing Performance Institute (MPI) resemble those of Western firms. One notable exception: China represents a disadvantage in customer reject rates. China has a median 50,000 parts per million (ppm), compared to 100 ppm in the U.S.

Time to Rethink China

by Grant Thornton LLP October 5, 2009 World Trade 100 White Paper

A recent survey by Square Trade shows that 1 in 3 laptops die in the first 3 years of use (a survey by Square Trade on warranty issues for 30,000 laptops sold in a 3 year period).

20.4 percent of failures are due to hardware malfunctions. 10.6 percent are due to drops, spills, or other accidental damage. Corrosion has played a role.



The Environment Impacts Reliability

- Reliability of electronics / components / systems is impacted by many factors
- Some factors we can easily control by controlling the environment that we manufacture parts in
- However, it is difficult to manage the environment where parts are shipped, stored or put into application
- What risk factors are we exposing our electronics to?
 - Atmospheric Pollution / Biological Attack / ESD Damage
 - Humidity / Gases
 - Volatiles in Packaging / Dust



The snow on the west side of Mount Hood is now grey

The east side remains white - Pollution is not regional with Air streams...

Corrosion has recently become a more significant factor in the reliability of electronic devices and components, reliability of assembled equipment, and even the reliability and performance of turbine equipment and heavy earth moving equipment. The world is increasingly more polluted and current packaging schemes are not keeping pace with the changes.



Some Corrosive Gases of Most Concern


- Nitrous Oxides (NOx)
 - . Effluent from gas powered forklift trucks, etc.
- Ozone (O3) reactive oxygen
 - Ozone acts as an accelerant making corrosion happen faster
- Hydrogen Sulfide (H₂S) and Sulfur Dioxides (SO2)
 - H2S is the bigger concern it is 10X more reactive than SO2
 - SO2 needs dust particles or dirt in the air to be reactive why Asia is having a greater issue with SO2 than NAR
- Carbonyl Sulfide (COS)
 - · (very prevalent on oceans)
- Hydrogen Chloride (HCI)


Reliability Through Packaging





H2S Levels - Worldwide

- Average H2S level in US
- Europe
- Brazil (Brasil)
- Average Level of H2S outdoor (Shanghai)
- H2S found inside electronic manufacturing plants – Suzhou
- 7 ppb
- 15 ppb
- 640 ppb
- 800 ppb
- 1500 ppb











Sometimes the complexity or size of the component / part makes identifying problems difficult

6 weeks in Standard ESD Bags in India

Reliability Through Packaging



Recent Review of Crates by a customer in Costa Rica


- Recent survey of high end electronic equipment in Costa Rica, where they had been told that no corrosion issues existed
- Tools in the crates had been packed in foil
- Every tool opened and reviewed showed some signs of corrosion and some mold damage as well
- Foil is a passive barrier it only works with 100% Hermetic seal and RH levels less than 37%
 - A pin hole / nail hole will make foil ineffective and fail
 - Foil has limitations and can fail



Mold, Mildew and Bacteria

- Many molds and mildews secrete sulfur as a byproduct of respiration
- General Dynamics in the UK has seen an increase in the bio-burden on the electronics coming in from Asia (higher numbers of bacteria, mold, mildew)
 - Experiments were done with new boards coming in from Asia still in their original packaging
 - Bacteria and mold/mildew cannot reproduce in the presence of Copper
 - Intercept has been shown to kill bacteria and the bio-loading coming in on electronics
 - Shielding bags nor foil have no ability to kill mold, mildew or bacteria

2008 Engineered Materials, Inc. (EMI)






Corrosion and Electronics


- How does Corrosion damage show up in electronic devices, components, etc.?
 - Latent Defects
 - Soldering Problems
 - Low Yield
 - Increased Resistance
 - Reduction in Performance
 - Poor Connections
 - Physical Discoloration, Staining
 - Contamination

2008 Engineered Materials, Inc. (EMI










3 Weeks in China in a standard ESD Bag

Corrosion not only increases resistance of the metal, potentially over-stressing (remember EOS), it also destroys contacts, solderability and decreases functionality








Solving one problem, can create another one somewhere else...








Reliability Through Packaging




Lead-Free Printed Circuit Board Finishes

With SnPb soldering processes HASL [SnPb] has been the predominant board finish followed by NiAu and OSP. The following represent the most common board finishes to consider for a lead-free process.

Board Finish	Comment
Electroless Ni / Immersion Au	Recommended in JEITA Pb-free roadmap and predominant in Japan and EU. Highest cost process, but good corrosion resistance for onboard contact pads and suitable for wire bonding pads for COB designs.
HASL [SnAgCu or SnCu]	Recommended in JEITA Pb-free roadmap and commonly used in Japan.
OSP	High volume, lost cost alternative. Commonly used. Solderability more easily degraded by multiple reflows.
Immersion Ag	Good solderability and an increasingly significant board finish.
Immersion Sn	Commonly used in EU. Presence of carcinogenic thiourea in solutions has limited its use in USA.









SUB-MICROMETER ORDER CORROSION OF SILVER BY SULFUR VAPOR IN AIR STUDIED BY MEANS OF QUARTZ CRYSTAL MICROBALANCE

Jun'ichi SAKAI from Waseda University Tokyo, JAPAN

Paper presented at 16th International Corrosion Congress in Beijing, China 2005

The purpose of this study is to clarify the effect of temperature (T = 30-75), relative humidity (RH = 10-100%) and distance between sulfur source and silver surface (I = 1-12 cm) on sub-micron order corrosion of silver during exposure to sulfur vapor

The independence of the corrosion rate on relative humidity indicates that free sulfur directly reacts with silver and moisture does not play a major role in corrosion of electronic materials.





Packaging

- Growing regulatory and environmental concerns on packaging
 - Currently European legislation makes plastics with >100 ml of oil on/in 1 m3 of film non-recyclable, later this year the level drops to 40 ml (1.3 ounces)
 - Foil bags as well as Shielding Bags are non-recyclable which has European implications
 - Sustainable / recyclable / re-usable are no longer catch phrases, they are the standards that are beginning to be demanded
 - European legislation against volatile substances in packaging, including TRGS-615
- Consolidation of European environmental laws, now with the EU Constitution being ratified will begin to take place
- Already two additional items added to RoHS list in EU
- Green Packaging is the new push around the globe

Reliability Through Packaging



Environmental Legislation Also Hits US

North America

California has passed SB 20: Electronic Waste Recycling Act of 2003, or EWRA. This law prohibits the sale of electronic devices after January 1, 2007, that are prohibited from being sold under the EU RoHS directive, but across a much narrower scope that includes LCDs, CRTs, and the like and only covers the four heavy metals restricted by RoHS. EWRA also has a restricted material disclosure requirement.

Effective January 1, 2010, the California Lighting Efficiency and Toxics Reduction Act applies RoHS to general purpose lights, i.e. "lamps, bulbs, tubes, or other electric devices that provide functional illumination for indoor residential, indoor commercial, and outdoor use."[23]

Other US states and cities are debating whether to adopt similar laws, and there are several states that have mercury and PBDE bans already.



Preservation Methods

- Dry Packaging (Foil) Passive Barrier
 - MVTR is key
 - Developed by the Germans in the 1920's
 - If you keep Ferrous Metals at less than 37% humidity the surface will become passivated
 - Limitations:
 - Requires high barrier properties
 - Requires hermetic sealing, evacuation and desiccants
 - Does not work for Non-Ferrous metals
 - Does not work if you loose vacuum or if you have an incomplete seal or tear or pinhole in the packaging
 - Is not recyclable and difficult to re-seal for post QA
 - Cannot be repaired easily after customs opens it

2008 Engineered Materials, Inc. (EMI

Reliability Through Packaging



Preservation Methods

- Shielding Bags
 - Do not provide MVTR or anti-corrosion properties
 - Developed by 3M in the 1970's
 - Metal in structures use ESD coatings on both inside on the poly surface and outside on the polyester surface – contain VOC's
 - Limitations:
 - Humidity dependent
 - Effective shelf / useful life reduced by time and temperature
 - Metal in structures can hold up to 560 volts of retained voltage
 - » Retained voltage is the energy required for the static electricity to bridge the PET layer to get to the metal layer in order to get to ground
 - They are not recyclable


2008 Engineered Materials, Inc. (EMI)



There is an alternative

- The Intercept Technology™
 - Developed by Bell Labs to provide:
 - Permanent, humidity independent ESD protection
 - ESD protection with no volatiles
 - ESD protection that also provides long term, noncontaminating corrosion protection
 - Effective, long term (proven) solderability protection
 - Intercept is TRGS-615 compliant
 - Static Intercept® is the best ESD Corrosion Protection material on the market today

© 2008 Intercept Technology Group (ITG





Carbon Footprints

A Telecommunication company did an investigation as to how best to reduce their carbon footprint / impact on the environment

Operation	Static Intercept®	Shielding Bags / Foil
Manufacture (10" x 20" bag)	36 kg CO2 36 % reduction	56 kg CO2
Recyclable / Re- usable	Yes ~50% reduction	No
Improvement in Reliability	1% Improvement (circuit cards)	
Savings by not having to remake cards / longer life	40 times reduction (4000% reduction)	

Reliability Through Packaging



Intercept Environmental Aspects

- Intercept helped VW to win 2 environmental awards by eliminating oiling their engine blocks with huge cost savings
- Intercept was awarded an Environmental Award for Being an Environmentally Friendly Anti-Corrosion Packaging by the German Government

The only anti-corrosion packaging in Germany with this honor

- -Intercept is RoHS compliant and keeps Silver from tarnishing so as to help RoHS compliant board finishes to stay pristine
- Intercept is fully recyclable / re-usable / VOC free / Volatile Free
- Intercept has been shown to kill mold and mildew



Intercept Technology

- Solves Corrosion problems causing defects in electronics and assemblies
- Replaces FOIL BARRIER and/or Shielding Bag packaging and traditional corrosion prevention systems – including volatile protection systems
- Is a reactive barrier system, not a passive system like foil systems or volatile systems
- Is inherently clean avoids contamination of sensitive components
- Provides passive mildew protection
- Provides protection for surfaces to be painted

© 2008 Intercept Technology Group (ITG)







Going Green Saves More than the Environment



A major automotive supplier in Japan has switched from a shielding bag (non-recyclable) and a RP oxygen absorber, cost 80 yen. The system is a 1 time use.

New system is an Intercept tray with 7 time re-use. The cost is 300 yen. The savings per year is a minimum of 27,000,000 Yen

18 months of trials - no rejects

2008 Engineered Materials, Inc. (EMI

Intercept® - flexibility and variety.... • Static Intercept comes in many forms - 3 mil film and bags • This is our stock items • For most applications - 4 mil film and bags • For export shipment • For Long Term Storage • Should be used for any customer testing - Shrink Film (7 and 8 mil) • For outdoor applications - Totes (heavy gauge sheet)

© 2008 Intercept Technology Group (ITG)

Intercept Technology



Intercept Technology™ Available Worldwide

Americas www.StaticIntercept.com

www.Intercept-Technology.com

Europe/India/Asia