




# PM220 Series

## Features

- Superior quality module made in Taiwan
- Good conversion efficiency of solar module
- Effectively minimize the power drop by the shade
- Produced for high durability to endure severe environmental elements
- High quality glass provides for less reflection of incoming sunrays

## Technical Drawing



## Product Characteristics

Electrical Characteristics: Performance at STC\*

Model Type	PM200	PM205	PM210	PM215	PM220	PM225	PM230	PM235	PM240	PM245
Peak Power, Pmax	200W	205W	210W	215W	220W	225W	230W	235W	240W	245W
Power Tolerance	± 3%	± 3%	± 3%	± 3%	± 3%	± 3%	± 3%	± 3%	± 3%	± 3%
Peak Power Voltage, Vpm	27.64 V	27.81 V	27.98 V	28.04 V	28.38 V	28.49 V	28.83 V	29.12 V	29.29 V	29.46 V
Peak Power Current, Ipm	7.25 A	7.30 A	7.45 A	7.63 A	7.76 A	7.81 A	7.92 A	8.03 A	8.23 A	8.28 A
Open Circuit Voltage, Voc	35.92 V	36.03 V	36.03 V	36.09 V	36.33 V	36.51 V	38.87 V	37.16 V	37.16 V	37.22 V
Short Circuit Current, Isc	7.90 A	7.94 A	8.00 A	8.19 A	8.31 A	8.38 A	8.48 A	8.58 A	8.79 A	8.84 A
Power Density [ W / ft <sup>2</sup> ]	11.20	11.48	11.76	12.04	12.32	12.60	12.88	13.16	13.44	13.72
Power Density [ W / m <sup>2</sup> ]	120.55	123.57	126.58	129.60	132.61	135.62	138.64	141.65	144.67	147.68
Module Efficiency	12.06%	12.36%	12.66%	12.96%	13.26%	13.56%	13.86%	14.17%	14.47%	14.77%
CEC	Listed	Listed	Listed	Listed	Listed	Listed	Listed	—	—	—
CEC PTC** Rating [W]	177.7	182.3	186.3	190.9	195.4	200.0	204.6	—	—	—
FSEC	In Progress	In Progress	In Progress	In Progress	In Progress	In Progress	In Progress	—	—	—

\*STC: Standard Test Condition, 1000W/m<sup>2</sup>, AM 1.5, 25°C

\*\*PTC: PVUSA Test Condition, 1000W/m<sup>2</sup>, 20°C, Wind speed 1 m/s at 10 meters above ground level. For details, please refer to the following URL: <http://www.gosolarcalifornia.ca.gov/equipment/pvmodule.html>


## System Integration Parameter & Safety Rating

Maximum System Voltage (U.S. & Canada)	600VDC
Maximum System Voltage (Area Not in the U.S. & Canada)	1000VDC (According to Norms in Each Area)
Series Fuse Rating	15A
Fire Safety Class	Class C
Application Class	Class A (Safety Class II)
Environmental Operating Temperature (°F, °C)	-40 to 185°F, -40 to 85°C

## Thermal Characteristics

NOCT (Nominal Operating Cell Temperature) °F, °C	111.56°F, 44.2°C
Temperature Coefficient TK Isc (Short Circuit Current) α	+0.123%/ °C
Temperature Coefficient TK Voc (Open Circuit Voltage) β	-0.296%/ °C
Temperature Coefficient TK Pmax (Peak Power) γ	-0.376%/ °C

### Current-Voltage Characteristics (I-V Curve) at Various Irradiance Levels



### Component Materials

Cell Qty per Module	60pcs
Cell Type	Polycrystalline Silicon
Cell Dimensions	6x6 in (156x156 mm)
Laminate Construction	Front: Tempered Glass Encapsulation: Solar Cells Embedded in EVA (Ethylene-Vinyl-Acetate) Rear: Tedlar Color of Back Sheet: White
Glass	Low-Iron Tempered Glass Standard Thickness: 0.126 in (=3.2mm) (>0.126in (=3.2mm), ex. 0.157in (=4mm) or above, custom-made possible.)
Junction Box	IP65, Kit with Solar Cables & Connectors, TÜV Certified & UL Listed
Bypass Diodes	3pcs, TÜV Certified & UL Listed
Cable	Solar Cable x2 (Kit with Junction Box & Connector) Cable Length: 39.37/39.37in. (1000/1000mm) Wire Size: AWG #12, 4.0mm <sup>2</sup> , TÜV Certified & UL Listed
Connector	Tyco Connectors, x2 (Male Coupler x1 + Female Coupler x1) MC4 Connectors (Optional), x2 (Male Coupler x1 + Female Coupler x1) TÜV Certified & UL Listed
Frame	Anodized Aluminum Frame. Color: Silver

### Physical Specifications

Dimension [L x W x H]	65.32 x 39.37 x 1.65 in (1659 x 1000 x 42 mm)
Module Area	17.86 sq. ft (1.66m <sup>2</sup> )
Weight	46.30Lbs (21Kg)

### Packing Specifications

Modules Per Carton	12pcs/carton
Modules Per Pallet	24pcs/pallet (=2 Cartons/Pallet)
Pallet Dimension [L x W x H]	66.7x44.7x44.2 in (1694x1134x1122mm)
Pallet Weight	1203.7 Lbs (546Kg)
20ft Container Capacity (pcs)	288
40ft Container Capacity (pcs)	672
53ft Container Capacity (pcs)	864

### Certification, Norm Passed, & Incentive

ISO 9001:2000 Quality Management	SGS Certified
IEC 61215:2005	TÜV certified
IEC 61215:2005 10.16	Passed & Complied with Mechanical Load Test for Heavy Snow Load
EN 61730-1 & EN 61730-2:2007	TÜV certified
UL1703 Ed:3 Rev:2004	Intertek Certified According to Safety Standard in the U.S.
ULC/ORD-C1703-01 Second Edition	Intertek Certified According to Safety Standard in Canada
IEC 61701 First Edition 1995.3	Passed & Complied with Salt Mist Corrosion Test Standard
CEC Listing	<a href="http://www.gosolarcalifornia.ca.gov/equipment/pvmodule.html">http://www.gosolarcalifornia.ca.gov/equipment/pvmodule.html</a>
FSEC Listing	In Progress

### Limited Warranty\*\*\*

Product	5Years
90% Output	10Years
80% Output	25Years

\*\*\*For details, please read our warranty letter.



Though the technical information has been carefully verified and corrected, error data could still be misplaced within. Above data will be subject to change without prior notice due to actual manufacturing condition and design. Please surf for the latest updates on RITEK websites, or contact us:

Headquarters, Taiwan: RITEK Corporation [www.ritek.com](http://www.ritek.com) [www.riteksolar.com](http://www.riteksolar.com)  
No.17, Kuang-Fu N. Rd., Hsin-Chu Industrial Park, Hu-Kou Township, Hsin-Chu County, 30351 Taiwan  
E-mail: [ritsolar@ritek.com.tw](mailto:ritsolar@ritek.com.tw)  
For Global Sales Contact: Tel: +886-3-5985696 Ext. 4011, 4013, 4014, 4015  
For Local Sales Contact in Taiwan: Tel: +886-3-5985696 Ext. 4020  
Fax: +886-3-5985249

(RITEK USA) Advanced Media, Inc. [www.ritekusa.com/green](http://www.ritekusa.com/green)  
1440 Bridge Gate Dr., Suite 395, Diamond Bar, CA91765, USA  
E-mail: [solarsales@ritekusa.com](mailto:solarsales@ritekusa.com) Tel: +1-909-861-2269 Fax: +1-909-612-4258

(RITEK Europe) Conrexx Technology B.V. [www.conrexx.com](http://www.conrexx.com)  
Keurmeesterstraat 18, 2984 BA Ridderkerk, The Netherlands  
E-mail: [solar@ritek-europe.com](mailto:solar@ritek-europe.com) Tel: +31-180-44-16-66 Fax: +31-180-44-16-67

(RITEK China) Kun-Shan RITEK Trading Co., Ltd [www.ritek.com.cn](http://www.ritek.com.cn)  
88, Second Avenue, Kun-Shan Export Processing Zone, Jiang-Su Province, 215301 China  
E-mail: [market@hutek.com.cn](mailto:market@hutek.com.cn) Tel: +86-512-57358989, Ext. 5566 & 5502 Fax: +86-512-57359090