

G750 .75A (750mA) 6V & 12V **Multi-Purpose Battery Charger** geniuschargers.com

Automatically Diagnoses, Recovers, **Charges & Maintains Your Batteries!** Now that's Smart...Wicked Smart!



The G750 is a smart, 5 Step, fully automatic switch-mode battery charger and maintainer. The G750 is best for small battery applications from 1.2-30Ah, such as charging your Motorcycle, ATV, Jet Ski or Snowmobile. In addition to charging, the G750 can effectively maintain any 6V or 12V batteries in larger applications, such as Cars, RVs, Boats and Trucks.

Wicked Smart Features



6V/12V COMPATIBILITY

Charges 6V & 12V batteries



Returns to last selected mode when restarted



FULLY INTERACTIVE

Automatically adjusts itself to changing current needs



Reverse polarity, short circuit, open circuit, spark proof, overheat, overcurrent & overcharge



MULTIPLE BATTERY CHEMIS

Safely charges Wet, Gel, MF & AGM batteries



EXTENDABLE CONNECTORSPlug-n-play connectors for easy accessory changes



HF/HE SWITCH MODE DESIGN
High-frequency, high-efficiency for a lightweight, compact charger



RAPID CHARGING TECHNOLOG Charges batteries 2X faster than traditional linear battery chargers



VARIABLE INPUT COMPENSATED

100% full charge even with varying A/C input voltages



ABNORMALITY PROTECTION Automatically shuts "off" if charger

remains in Bulk charge mode for an extended period of time

POWERED BY



NOCO VosFX Proces

The VosFX Processor is a revolutionary smart processor utilizing sophisticated levels of intelligence to alter the charge process, based on organic feedback from the battery, to extend battery life. The VosFX Processor quickly and efficiently makes decisions on how to charge the battery without risking user safety or damage to the battery.




Multi-Purpose Battery Charger

Automatically Diagnoses, Recovers, Charges & Maintains Your Batteries!

Now that's Smart...Wicked Smart!

Charging Steps



Step 1: Diagnostics

Checks the battery voltage to make sure battery connections are good and the battery is in a stable condition before beginning the charge process.

Step 2: Soft Start

Begins Bulk charging process with a gentle (soft) charge.

Step 3: Bulk

Continues Bulk charging process, returns 90% of battery capacity.

Step 4: Absorption

Brings the charge level to 100%. The battery charger will deliver small amounts of current to provide a safe, efficient charge and limit battery gassing.

Step 5: Maintenance

Monitors the battery voltage continuously to determine if a maintenance charge should be initiated. If the terminal voltage falls below approximately 6.4V (6V) and 12.8V (12V), the charger will start the Maintenance cycle until voltage reaches approximately 7.2V (6V) and 14.4V (12V) and then will discontinue the charge cycle. Maintenance cycle is repeated indefinitely to keep the battery at full charge, without overcharging. The battery charger can be left connected indefinitely.

Technical Specifications

Input Voltage AC 110-120VAC, 50-60Hz
Working Voltage AC 85-130 VAC, 50-60Hz
Input Current 300mA RMS Max
Efficiency 85% Approx.

Power 20W Max

Charging Voltage 7.2V/14.4V
Charging Current 750mA

Back Current Drain <5mA

Ripple <2%

Charger Type 5 Step, Fully Automatic,

Switch-Mode

Type of Batteries 6V & 12V Lead-Acid

Battery Chemistries Wet, Gel, MF & AGM
Battery Capacity 1.2-30Ah, Maintains All

Battery Sizes

Housing Protection IP60

Cooling Natural Convection

Noise Level <50 dB

Dimensions (L x W x H) 4.5 x 2.7 x 1.3 Inches

leight 0.5 Pounds

5 Year Limited Warranty

What's In The Box

- G750 Charger
- Battery Clamp Connectors
- Eyelet Terminal Connectors
- Owner's Manual & User Guide





Follow Us At:



Safely Charges Wet, Gel, MF & AGM Batteries geniuschargers.com