

2 Horse, SxS, Bumper Pull Models:

Available in Front Face or Rear Face configuration

12' or 14' in length

6' 4" or 6' 10" in width

7' or 7' 6" in height

Standard Features:

- 100% aluminum frame and body built to CMVSS/FMVSS standards
- .125 (1/8) aluminum, aircraft grade, resistant to road salt ,marine environments and disinfectants
- All fittings and fasteners stainless steel or aluminum
- 2" bulldog coupler with lock
- Fulton aluminum hitch jack with double jockey wheel
- Aluminum 5-Star rims and Goodyear tires (includes full size aluminum spare)
- Electric brakes on all wheels with on board breakaway battery (auto charge)
- Rubber torsion axles, independent suspension
- Standard double rear doors, or optional EZ Lift Ramp
- Exterior horse ties (2 on each side)
- LED lights
- 2-wire isolated electrical system
- Remotely operated courtesy lights
- Front side access door with lock
- All openings are automotive bulb sealed
- Aerodynamic air deflector on upper rear
- Trailer accessory kit, including horse first aid kit and other essentials



Horse Area:

- Double aluminum walls, insulated up to 48" in horse compartment
- 1/2" rubber, non-skid flooring in horse area
- Horse divider with swinging feature, fully removable
- Breast bar with safety breakaway feature, butt bars, both removable and adjustable
- Padding on divider, side walls, breast and butt bars as well as head protection in stalls and on entrance
- Interior horse ties, manger ties and hay net / water bucket attachments
- 2- Interior LED lights with switch at the door
- Tinted, sliding, screened, safety barred window each side drop down windows available
- 2 3 way vents on roof
- NASA SUPER-CERAMIC insulation on inside ceiling and outside roof

Tack storage:

- Saddle rack for each horse (2)
- 2 bridle hooks for each horse (4)
- Blanket bar for each horse (2)
- 2 storage bins in the front area

Many optional upgrades are available.

Call (204) 594-9455 for more information.