



CP350SLG Standby UPS

Provides battery backup, power protection and energy savings for home/office computers and connected electronics.

Recommended for home and office users for reliable surge protection and battery backup

- 350VA / 255W
- GreenPower UPS™ design
- 6 Outlets
- Widely-Spaced Outlets
- RJ11 Protection
- EMI/RFI Filters
- Full-time Surge Protection
- Compact Form



CyberPower's patented GreenPower UPS™ technology reduces UPS energy costs up to 75%! Save money and help reduce carbon emissions.

Visit CPSww.com to learn more about CyberPower's power solutions.

CyberPower UPS Awards



The CyberPower Standby CP350SLG uninterruptible power supply (UPS) safeguards PCs, monitors, cable DSL/modems, VoIP routers, fax machines, and home theater equipment from blackouts, brownouts, surges, spikes, sags, and other power abnormalities. Its composite integrated circuitry offers advanced surge protection. Patented GreenPower UPS™ circuitry reduces UPS energy costs by up to 75% compared to competitive models.

The CP350SLG unit has a capacity of 350VA/255Watts, six (6) NEMA 5-15R receptacles, including two (2) widely-spaced outlets to accommodate transformer-based plugs. Its compact design allows for horizontal or vertical placement. This UPS has a maintenance-free 12V/3.6Ah battery. Protection for phone/network (RJ11) is also included. EMI/RFI filters protect against electromagnetic interference and radio frequency signals—preventing line noise (“humming”) over telephone lines or audio systems.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material and workmanship. The CP350SLG UPS is protected by a \$75,000 Connected Equipment Guarantee.

FEATURES & BENEFITS:

Energy-saving Technology: Patented GreenPower UPS™ advanced circuitry reduces UPS energy costs by up to 75% compared to competitive models.

Ultra-quiet Operation: One of the lowest sound emissions of any UPS in its class.

EMI/RFI Filters: Shielding against electromagnetic interference and radio frequency signals prevents line noise (“humming”) over telephone lines or audio systems.

Transformer-spaced Outlets: Widely-spaced outlets accommodate large transformer-based plugs without compromising the utility of other outlets.

Compact: Rugged construction and small footprint make this perfect for areas with limited space.

LED Indicators: LED status lights indicate Power-On and Wiring faults.

Audible Alarms: Distinctive tones identify when the unit is running on battery power, if it is overloaded or when the battery is low.

Resettable Circuit Breaker: The user may use this convenient unit reset switch in case of an overload.

Technical Support: CyberPower assists users with any product, installation, or warranty concerns – free of charge.

3-Year Warranty: Stringent manufacturing processes and innovative product design enables CyberPower to offer one of the strongest warranties in our industry. CyberPower will replace damaged units within three (3) years of purchase date.

ISO and Safety Certifications: All CyberPower manufacturing facilities are state-of-the-art and ISO-9001 Quality Tested. Our products are certified by the FCC, cUL, and UL.

CP350SLG SPECIFICATIONS

GENERAL	
UPS Topology	Standby
Energy Saving	GreenPower UPS™ technology
INPUT	
Voltage	96Vac - 140Vac
Frequency	47Hz/63Hz
Plug Type	NEMA 5-15P
Plug Style	Right angle, 45-degree, offset right
Cord Length	5'
Surge Protection	10 Amp
OUTPUT	
VA	350
Watts	255
On Battery Voltage	120Vac ± 5%
On Battery Frequency	50/60Hz ± 1%
On Battery Waveform	Simulated sine wave
Outlet Type	NEMA 5-15R
Outlets - Battery & Surge Protected	3
Outlets - Surge-Only Protected	3
Outlets - Widely Spaced	2
BATTERY	
Runtime at Half Load (127W)	8 minutes
Runtime at Full Load (255W)	2 minutes
Battery Type	Sealed lead acid
Battery Size	12V/3.6AH
User Replaceable	No
Typical Recharge Time	8 Hours
Battery Quantity	1
SURGE PROTECTION AND FILTERING	
Surge Suppression	810 Joules
Phone Protection RJ11	1-In, 1-Out
EMI/RFI Filtration	Yes
MANAGEMENT & COMMUNICATIONS	
LED Indicators	Power on, wiring fault
Audible Alarms	On battery, low battery, overload
Software	None
PHYSICAL	
Dimensions (WxHxD)	7.1" x 4.3" x 3.2"
Weight (lbs)	3.5
Keyhole Mounting Slots	None
CERTIFICATIONS	
Certifications	UL1778, cUL 107.3, FCC DOC Class B
ROHS	ROHS Compliant
WARRANTY	
Product Warranty	3 Years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$75,000

Product Detail

