

RIGID LIFELINES™ SELF-RETRACTING LANYARDS

Rigid Lifelines™ Cable and Web Self-Retracting Lanyards (SRLs)

Rigid Lifelines™ self-retracting lanyards are built tough, providing workers with a reliable safety partner for overhead fall arrest and fall restraint applications. Available in corrosion-resistant plastic, zinc plated steel, and stainless steel housings, our SRLs stand up to aggressive conditions both indoors and outdoors. During a free fall, cam-driven locking pawls are activated, ensuring that the fall is arrested within 2 feet (.6m) or less. All Rigid Lifelines™ SRLs will reduce fall forces imposed on a worker to 900 lbs. (4kN) Maximum Arresting Force (MAF) or less. Workers can feel secure knowing that our SRL's fast lock-up speed will limit total fall distance.

Model 4015 Features (Z359.1 Compliant)

- Supports 1 worker/tools with a combined max. weight of 310 lbs.
- 18 feet of 3/16 inch Galvanized aircraft cable.
- Lightweight and rugged thermoplastic case design.
- Zinc plated forged steel hooks provide superior strength.
- Red fall indicator on top swivel allows for easy inspection.
- Two independent cam-driven pawls help prevent freezing in place due to debris.

Model 4020 Features (Z359.1 Compliant)

- Supports 1 worker/tools with a combined max. weight of 310 lbs.
- 20 feet of 1 inch polyester webbing.
- Lightweight and rugged thermoplastic case design.
- Zinc plated forged steel hooks provide superior strength.
- Red fall indicator on top swivel allows for easy inspection.
- Two independent cam-driven pawls help prevent freezing in place due to debris.



MODEL	LENGTH	WEIGHT	HEIGHT	WIDTH	DEPTH	CASE	LINE	CAPACITY
8-4015	18' (5.4m)	7.5 lbs. (3.4kg)	22" (55.9cm)	6.5" (16.5cm)	3" (7.6cm)	Thermoplastic	3/16" Galvanized Cable	310 lbs.
8-4020	20' (6.1m)	6.8 lbs. (3kg)	20" (50.8cm)	6.5" (16.5cm)	3" (7.6cm)	Thermoplastic	1" Polyester Webbing	310 lbs.

rigidlifelines.com

Toll Free: (800) 869-2080
Local: (610) 286-7200
Fax: (610) 286-0085



RIGID LIFELINES™ SELF-RETRACTING LANYARDS

Models 4030 and 4050 Features (ANSI A10.14, Z359.1 Compliant)

- Supports one worker/tools with a combined max. weight of 310 lbs.
- 30 or 50 feet of 3/16 inch Galvanized aircraft cable.
- Zinc plated full steel cases provide a durable, corrosion-resistant unit.
- Brass brakes provide reliable operation and long life.
- Forged steel snaphooks with load indicating swivels.
- Three independent cam-driven pawls help prevent freezing in place due to debris.

Models 4031 and 4051 Features (ANSI A10.14, Z359.1 Compliant)

- Engineered for harsh working environments, including applications based near salt water or clean room environments.
- Supports one worker/tools with a combined max. weight of 310 lbs.
- 30 or 50 feet of 3/16 inch stainless steel cable.
- Both units manufactured of non-corrosive metals and composites, and stainless steel housings.
- Stainless steel snaphooks with stainless steel load indicating swivels.
- Three independent cam-driven pawls help prevent freezing in place due to debris.



MODEL	LENGTH	WEIGHT	HEIGHT	WIDTH	DEPTH	CASE	LINE	CAPACITY
8-4030	30' (9.1m)	25 lbs. (11.4kg)	28" (71.1cm)	9.5" (24.1cm)	5" (12.7cm)	Steel	3/16" Galvanized Cable	310 lbs.
8-4031	30' (9.1m)	25 lbs. (11.4kg)	28" (71.1cm)	9.5" (24.1cm)	5" (12.7cm)	Stainless Steel	3/16" Stainless Steel Cable	310 lbs.
8-4050	50' (15.2m)	26.8 lbs. (12.2kg)	28" (71.1cm)	9.5" (24.1cm)	5" (12.7cm)	Steel	3/16" Galvanized Cable	310 lbs.
8-4051	50' (15.2m)	28 lbs. (12.7kg)	24" (61cm)	9.5" (24.1cm)	5" (12.7cm)	Stainless Steel	3/16" Stainless Steel Cable	310 lbs.

rigidlifelines.com

Form #: RLL-SRL0611V3

Copyright 2011 © Rigid Lifelines™ All Rights Reserved.

Toll Free: (800) 869-2080
Local: (610) 286-7200
Fax: (610) 286-0085

