



Telco Depot
34 Cleveland Ave.
Bay Shore, NY 11706
Toll Free: 800-390-1200
International: 631-964-5000
<http://www.Telcodepot.com>
info@telcodepot.com

Yealink SIP-T38G Gigabit Color IP Phone w/Power Supply

Yealink SIP-T38G VoIP Phone

TelcoDepot.com, your preferred telecommunications partner, has always led the way in providing quality service with our industry-leading expertise in IP PBX Phone Systems and Support Services.



The Yealink SIP-T38G IP Phone is Yealink latest innovation designed for executives with demanding collaborative communication needs. For managers, it is a future-proofing network investment which supports seamless migration to GigE-based network infrastructure. Dual-port Gigabit Ethernet is designed for flexible deployment options and lower cabling expenses. With its high-resolution TFT color display, The T38G IP Phone offers a brilliant depiction of caller's information. Meanwhile, the user interface was designed for clarity and intuitive operation. Moreover, Equipped with the TI Aries chipset, HD handset, HD speaker and HD codec (G.722), The T38G IP Phone offers an unrivaled, lifelike audio experience. Furthermore, The Yealink T38G VoIP Phone supports the security standards which prevent the recording of data, For instance: TLS, SRTP, HTTPS, 802.1x, Open VPN and AES encryption. Like all other Yealink VOIP phones this is an excellent choice for use with our Hosted PBX Service.

Future-proof IP Phone

- Dual-port Gigabit Ethernet, Power over Ethernet
- 4,3" TFT-LCD, 262K colors, Intuitive user interface
- TI Aries chipset and TI voice engine
- HD Voice: HD Codec, HD speaker, HD handset
- 6 VoIP accounts, BLF/BLA, IPV6, OpenVPN
- Headset, Support Wireless Headset, LCD Expansion module
- Includes Power Adapter

Available at [TelcoDepot.com](http://www.telcodepot.com) for only \$249.00 – Call 1 800 390 1200 for more information or visit:
<http://www.telcodepot.com/products/yealink-sip-t38g-gigabit-color-ip-phone-wpower-supply/1019>

Yealink T38G Phone Features

- 6 VoIP accounts, Hotline, Emergency call
- Call hold, Call waiting, Call forward, Call return
- Call transfer (blind/semi-attended/attended)
- Caller ID display, Redial, Mute, DND
- Auto-answer, 3-way conferencing
- Speed dial, SMS, Voicemail
- Message Waiting Indication (MWI) LED
- Tone scheme, Volume control
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Phonebook (1000 entries), Black list
- Call history: dialed/received/missed/forwarded
- Menu-driven user interface
- Localized language and input method
- Soft keys programmable
- Supports up to 6 expansion modules(EXP39)
- Supports Wireless Headset Adapter(EHS36)

Advanced Features

- XML phonebook search/import
- LDAP phonebook
- XML Idle Screen
- Action URL & Active URI
- Background Pictures, Screensaver
- Color Picture Caller-ID
- Theme, Screen Sleep

IP PBX System Integration

- Busy lamp field (BLF), BLF list, (BLA)
- DND & Forward synchronization
- Intercom, Paging, Music on hold
- Call park, Call pickup
- Call recording, Call completion
- Group listening, Group pickup
- Anonymous call, Anonymous call rejection
- Network conference
- Distinctive ringtone
- Dial Plan, Dial-now

Yealink T38G Codecs and Voice Features

- Wideband codec: G.722
- Narrowband codec: G.711 μ /A, G.723.1
- G.726, G.729AB
- VAD, CNG, AEC, PLC, AJB, AGC
- Full-duplex speakerphone with AEC

Yealink T38G Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- IPV6
- DNS SRV (RFC3263)
- Redundant server support
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info
- Proxy mode and peer-to-peer SIP link mode
- IP Assignment: Static/DHCP/PPPoE
- Bridge/router mode for PC port
- TFTP/DHCP/PPPoE client
- Telnet/HTTP/HTTPS server
- DNS client, NAT/DHCP server
- Logout

Yealink T38G Management

- Auto-provision via FTP/TFTP/HTTP/HTTPS
- Auto-provision with PnP
- SNMP V1/2 optional, TR069 optional
- Configuration: browser/phone/auto-provision
- Factory configuration customized
- Trace package and system log export

Yealink T38G Security

- Open VPN, 802.1x, VLAN QoS (802.1pq), LLDP
- Transport Layer Security (TLS)
- HTTPS (server/client), SRTP (RFC3711)
- Digest authentication using MD5/MD5-sess
- Secure configuration file via AES encryption
- Phone lock for personal privacy protection
- Admin/VAR/User 3-level configuration mode

Yealink T38G Physical Features

- TI Aries chipset
- 4.3" TFT-LCD, 480 x 272 pixel, 262K colors
- 48 keys including 16 programmable keys
- 1xRJ9 (4P4C) handset port
- 1xRJ9 (4P4C) headset port
- 2xRJ45 10/100/1000Mbps Ethernet ports
- 1XRJ12 (6P6C) EXT port
- Power adapter: AC 100~240V input and DC 5V/1.2A output
- Power over Ethernet (IEEE 802.3af)
- Power consumption: 1.6-2.6W
- Net weight: 1.05KG
- Dimension: 273x204x42MM
- Operating humidity: 10~95%
- Storage temperature: up to 60°C

www.TelcoDepot.com

Call 1-800-390-1200

info@TelcoDepot.com