

True Day / Night Vision Outdoor HD IP Camera

- **O** 720p HD Video (1280x720) & 2 Way Audio
- Triple Video Streams H.264, MPEG-4 and M-JPEG
- Multiple Streaming Protocols (HTTP, HTTPS, RTSP...)
- O Live Streaming to iPhones, iPads, Android, etc.
- O Supports 802.11N Long Range Wireless
- O Built-in InfraRed (IR) LEDs for Night Vision
- O Built-in IR-cut Switch for True Colour Video
- Built-in 32Gb Micro-SD card for On-board Video Storage
- Built-in SMB/CIFS Client for Direct Recording to NAS



A compact, all-in-one IP camera that's big on value and performance...

The EyeSpy247EXT+ is an all-weather IP67 rated (water and dust proof) truly all-in-one indoor and outdoor IP CCTV camera. With a high quality progressive CMOS sensor, the camera is capable of streaming H.264, MPEG-4 and M-JPEG 'true colour' video up to 30fps, in 720p High Definition - even encrypted over HTTPS.

Plus it offers on-board recording to a Free preinstalled 32Gb micro SD card, automatic day/night switching, Infrared (IR) night vision, PIR and motion sensors, 2 way audio, long range 802.11N wireless connectivity and much more.

Windows, Mac and Linux friendly means easy local and remote viewing via most web browsers such as Internet Explorer, Firefox, Safari and Chrome as well as on iPhones/iPads, Android mobiles and other smart-phones.

Use it stand alone or link it with our unique online platform making it easy to view Live from anywhere with additional features including automated monitoring, off-site video recording, email/SMS event alerts, guest access and more.

Now it's easier and more affordable than ever to keep an eye on what's important to you, no matter where you are. Whether it's watching over your home or business, checking when your kids are back from school or looking in on elderly relatives EyeSpy247's complete solution of Internet camera and web based monitoring platform will keep you informed when it matters.

For more information

Web: www.eyespy247.com Email: info@eyespy247.com


0845 5440 288 Tel:







■ Illustation

Dimension Diagram







Front Panel

Rear Panel

Sensor and Lens

Image Sensor	1/4" CMOS Sensor
Minimum Illumination	0 Lux (with IR LED)
Lens	Board Mount Type, Fixed-Focal, Aperture F2.0
	Diagonal View Angle: 66° (Horizontal=57.8°, Vertircal=37.8°)
PIR Sensor	Detection Range 5 Meters (15 feet)

Video

Video Compression	H.264, MPEG-4 SP, M-JPEG
Video Streaming	Simultaneous H.264, MPEG-4 and M-JPEG, 3GPP Compatible
Image Settings	Flip, Mirror, Brightness, Sharpness, White Balance
Resolution and Frame Rate	720P (1280 x 720)VGA, QVGA, QQVGA, Up to 30 fps (frame per second)

Audio

Audio	Build-in Microphone and Speaker, Bi-directional Audio (Full-Duplex), G.711, G.726, LPCM
-------	---

■ Alarm and Event Management

Alarm and Event Management Motion Detec	on, PIR Sensor
---	----------------

■ Network

Ethernet	10/100 Base-T, Auto-MDIX
Protocols	TCP/IP, UDP, ICMP, DHCP, NTP, DNS, SMTP, FTP, HTTP, RTP, RTSP, RTCP, UPnP, DDNS, PPPoE,
	HTTPS, Bonjour, WINS
Wireless	IEEE802.11b/g/n, WEP64/128 bit, WPA/WPA2 Personal, WPS

Software

Applications	Setup Wizard, iPhone Live View Softwave
Web Browsers	Internet Explorer 6 or Later, Firefox, Google Chrome, Safari

→ Hardware

Connectors	RJ-45 for Ethernet
	DC Power Jack
	Internal Micro-SD Card Slot (Option)
Processors and Memory	SoC: ARM9
	Flash: 32 MB
	RAM: 128 MB
LED and Button	LED: Power
	Button: Reset
Night Vision	IR LED x 8
	Light Sensor x 1, Auto IR CUT Switcher, Range: Above 5 Metters
Power Consumption	12V DC / Max 4.8W
Compliance	CE, FCC
	Power Supply: UL
Dimensions (H x W x D)	103mm x 94mm x 37mm (4.1" x 3.7" x 1.5")
Weight	900g

Environment

Operation	Temperature: -10° - 50°C (14° - 122°F); Humidity: 10% - 85% RH (non-condensing)
Storage	Temperature: -20° - 70°C (-4° - 158°F); Humidity: 5% - 90% RH (non-condensing)

Accessories

Accessories	
Accessories	Power Supply (12V / 1A, 100-240VAC), LAN Cable, Quick Installation Guide, Stand