

The Cablecast SX2HD is a multi-format video server capable of playing a variety of SD and HD codecs. The SX2HD gives you two output channels and one encoder channel of SDI or HD-SDI with embedded audio. Also included is the Cablecast Framework — it's all you need to start programming your station!



WHY USE THE CABLECAST SX2 HD?

- Unparalleled deck and device control.
- Attaches to your network for easy data transfer from editing stations and external storage
- Easily share and play files from other facilities

KEY FEATURES

- Two output channels and one encoder channel
- Complete Cablecast programming and automation software included
- Plays MPEG-1 Layer 2 and Linear PCM, MPEG-2, MPEG-4, H.264, QuickTime, DVCPRO, DVCPRO50 and DVCPROHD.
- Includes the Carousel Framework for up to fifteen channels of community bulletin board
- Sixteen terabytes of usable storage, RAID-6 protected.

SPECS

| Network: | 10/100/1000base-TX |
|--------------------|---|
| Power: | 100-240V AC, 50/60Hz |
| Power Consumption: | approx. 200w |
| Power Supply: | Optional Redundant |
| Dimensions: | 19"x27.25"x5.25" (3RU) |
| Weight: | 52lbs. (Shipping) |
| Hard Disk: | 2TB RAID - 1 System 16TB RAID - 6 Content |
| Video Inputs: | 1 SDI / HD-SDI (BNC) (no analog video) |
| Audio Inputs: | 2 AES / EBU 2 SDI stereo embedded (no analog video) |
| Video Outputs: | 2 SDI / HD-SDI (no analog video) |
| Audio Outputs: | 2 AES / EBU 2 SDI stereo embedded (no analog video) |
| Genlock: | Tri-Level Sync |
| Encoding Formats: | SD: MPEG-2 IBP SD: DVCAM SD: DVCPRO |
| | HD: MPEG-2 I-Frame & IBP HD: DVCPRO HD |
| Playback Formats: | SD: MPEG-2 IBP SD: MPEG-4 SD: H.264 (AAC audio only) SD: AVI |
| | SD: DVCAM SD: DVCPRO SD: DVCPRO50 SD: DV in Quicktime wrapper |
| | HD: MPEG-2 I-Frame & IBP HD: DVCPRO HD HD: H.264 |

tightrope media systems *

800 Transfer Road, Suite 1B Saint Paul, MN 55114 866-866-4118 www.trms.com