



GXP1450 IP Phone is a 2-line with 2 SIP accounts next-generation enterprise grade SIP phone that delivers superior HD audio quality, rich and leading edge telephony features, automated provisioning, and personalized information. Combined with a **V2VIP™ Calling Plan**, this product is a cost effective choice for a SMBs and enterprise users needing an affordable, high-quality IP Phone.—**\$69.99**

- 2 dual line color keys
- Full-duplex hands free speakerphone
- 180x60 pixel graphic backlit LCD display
- HD wideband audio
- Automated personalized information (i.e. local weather)
- Auto-configuration provisioning
- Dual switched auto-sensing 10M / 100Mbps network ports
- Personalized music ring tone / ring back one
- Large phonebook up to 500 contacts



This budget-friendly SIP phone features: 2-line appearance, 180 x 60 graphic displays, 3 XML programmable soft-keys, 3-way conference and, integrated POE

Main Features

- **SIP Compliant and Protocols**—SIP RFC2361, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A record and SRV/NAPTR), DHCP, PPPoE, TFTP, NTP, STUN, SIMPLE
- **Network Interfaces**—Dual switched 10/100Mbps ports with integrated PoE
- **Graphical Display**—Back-lit 180x60 pixel graphical LCD display
- **Feature Keys**—2 line keys with dual color LED, 2 SIP accounts, 3 XML programmable soft keys, 5 navigation/menu/volume keys, 10 dedicated function keys (Hold, Speakerphone, Transfer, etc)
- **Voice Codecs**—Support G.723.1, G.729 A/B, G.711 u/a, G.726-32, G.722 (wide-band), iLBC, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)
- **Telephony Features**—Hold, transfer, forward, 3-way conference, call pickup, shared-call-appearance (SCA), bridged-line-appearance (BLA), call waiting, call log, customized screen / ringtone, auto-answer
- **HD Audio**—Speakerphone and Handset
- **Upgrade and Provisioning**—Firmware upgrade via TFTP/HTTP, mass deployment using central secure provisioning file
- **Quality of Service**—Layer 2 (802.1Q, 802.1p); Layer 3 (ToS, DiffServ, MPLS) QoS
- **Security**—User and administrator level passwords, MD5 and MD5 -sess based authentication, AES based secure based configuration file, SRTP, TLS



- **Power**—Universal power adapter (Input: 100-240VAC 50-60Hz; Output: +5VDC, 800mA, Integrated Power over Ethernet)
- **Physical**—Dimension: 186mm x 210mm x 81mm); Unit weight: 0.8kg
- **Temperature / Humidity**—32 - 104°F / 0 - 40°C, 10 - 90% (non-condensing)
- **Compliance**—FCC, CE, C-Tick

Additional Features

- Full-duplex speakerphone
- Headset jack (2.5mm and RJ22)
- 3-way conference
- Call Log
- Off-hook auto-dial
- Multi-language—English, Spanish, French, German
- Server redundancy, fail-over support
- Base stand with 2 angle positions
- Hold, Mute, Transfer, Forward
- Call Waiting
- Auto-answer
- Downloadable Phonebook

Make the Call and See!

Wind Currents Communications, Inc.

Tel: **845 247 5135** • Fax: **845 679 9472** • Toll-Free: **877 4BIZ V2VIP** (424 9828)

Email: **sales@wccivoip.com** • Web: **www.v2vipvideophones.com**