

Two Stage Wheeled Portable

Standard Features

- Heavy-duty two stage cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Finned intercooler
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Synthetic Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- 8 & 15 gallon tanks are low profile, powder coated twin tank receivers
- 17 and 30 gallon tanks are powder coated and ASME certified
- Convenient lifting handles
- Anti-vibration feet
- Pneumatic tire(s)
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor/engine starting
- Stainless steel braided discharge hose
- Tank gauge
- Regulator and outlet pressure gauge
- Pressure relief safety valve
- Designed, tested and proven to meet the demands of the construction and rental industry

Electric

- Constant run control set at 145-175 PSI
- High quality pilot valve
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- 6 ft power cord

Model	Pump	HP	Tank Gallon	Power Supply	CFM @ 100 PSI	CFM @ 175 PSI
GT5B-8P2	GT	5	8	230V 1 Phase	15.5	15.2
GT5B-15P2			15			
GT5B-17P			17			
GT5B-30P			30			
W5B-30P	W		30		18.1	17.9



GT5B-8P2



G8HGA-15P2

G8HGA-17P

Options (Electric Motor)

- Start-Stop control ■ Dual control
- Dual voltage switch ■ On-Off switch
- Two wheel option (8 & 15 gallon models)
- CSA option ■ Oil sight glass ■ Air line filter ■ Lubricator
- Other pressures available upon request

GT5B-30P



Model	Pump	HP	Tank Gallon	Drive	CFM @ 100 PSI	CFM @ 175 PSI
GT8HGB-8P2	GT	8	8	Honda GX Gasoline Engine Recoil	15.7	15.4
GT8HGB-15P			15			
GT8HGB-17P			17			
GT8HGB-30P			30			
W11HGB-30P	W	11	30	Start	17.8	17.6

Gasoline Engine

- Constant run control set at 145-175 PSI
- High quality pilot valve
- Pneumatic throttle idle control
- Honda GX Series OHV Engine

Options (Gas Engine)

- Two wheel option (8 & 15 gallon models)
- CSA option ■ Oil sight glass
- Air line filter ■ Lubricator ■ Electric start
- Other engine options available upon request
- Other pressures available upon request