

Stem Series

Datasheet



January 1, 2012
Subject to change

Stem Series

Overview

Features

- T-10 linear tube with G13 bi-pin
- 30,000 hour lifetime
- 3 year warranty
- RoHS, CE, UL

Benefits

- 16 watts per 4' tube
- No ballast factor
- UV/IR free light
- Low heat
- Mercury free
- Instant on
- T10 size and G13 bi-pin compatible with most existing T8/T12 fixtures

Applications

- Residential
- Retail
- Hospitality
- Restrooms
- Office
- Parking Garages



Stem 16 watt T-10 4' tube

Stem Series

Dimensions

Product	Diameter	Length
Stem 16 watt T10 G13	1214mm	30mm



Stem 16 watt T-10 4' tube

Stem Series

Technical - Light

Product Number	Lumens	CRI	CCT	Beam Angle	Lifetime
TBRT10-16-W-HU-C-N*	1060	80	3000K	160°	30,000 hrs
TBRT10-16-N-HU-C-N*	1100	75	4500K	160°	30,000 hrs
TBRT10-16-B-HU-C-N*	1450	75	6000K	160°	30,000 hrs
TBRT10-16-W-HU-F-N	1060	80	3000K	160°	30,000 hrs
TBRT10-16-N-HU-F-N	1100	75	4500K	160°	30,000 hrs
TBRT10-16-B-HU-F-N	1450	75	6000K	160°	30,000 hrs

* Features a clear lens.

Stem Series

Technical - General

Product Number	Watts	Base	Voltage	Frequency	Dimmable	Type
TBRT10-16-W-HU-C-N*	16	G13	80-277 V	50/60 Hz	No	Linear
TBRT10-16-N-HU-C-N*	16	G13	80-277 V	50/60 Hz	No	Linear
TBRT10-16-B-HU-C-N*	16	G13	80-277 V	50/60 Hz	No	Linear
TBRT10-16-W-HU-F-N	16	G13	80-277 V	50/60 Hz	No	Linear
TBRT10-16-N-HU-F-N	16	G13	80-277 V	50/60 Hz	No	Linear
TBRT10-16-B-HU-F-N	16	G13	80-277 V	50/60 Hz	No	Linear

* Features a clear lens.

Stem Series

Datasheet



© 2012 ON-Q LLC. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of ON-Q LLC or their respective owners.

Find us on the web at:
www.onqlighting.com