Class I, Div. I & II Emergency Lighting System - 90 Minutes - Explosion Proof Bug Eyes Exit Sign - 1 Part #: EXP-EMG-EXT-12W-2L



## Made in the USA

The EXP-EMG-EXT-12W-2L Explosion Proof Emergency Light with back up emergency battery and exit sign from Magnalight is rated Class 1 Division 1 Class II Division I & II and is an ideal emergency lighting solution for hazardous locations where failsafe lighting reliability is a must.

The EXP-EMG-EXT-12W-2L is an ideal solution for operators who wish to ensure their hazardous workspaces employ the most effective and reliable safety lighting options available. Under normal conditions this emergency lamp uses normal external power to illuminate its two 6 watt LED lamps. In the case of power outages or in any situation where power is interrupted, this unit automatically switches to a battery backup which will power the unit for 90 minutes or until power is restored. Once power is restored a built in charger will return the unit to a fully charged state within acceptable UL time limits.

This explosion proof emergency exit lighting fixture carries an integral maintenance-free, sealed, high temperature Nickel-Cadmium battery backup power supply. When external power is cut due to outages or accidents this lamp automatically switches to its battery backup which will power the LED bulbs for 90 minutes. The battery is protected from deep discharge by solid state circuitry which senses low voltage and turns off the unit before battery damage can occur.

This emergency exit light is multi-voltage capable and can operate with voltages ranging from 120V to 277V @ 50/60HZ. This unit's housing and LED light fixtures are constructed of copper-free aluminum that is epoxy powder coat finished to protect the aluminum surfaces. The EXP-EMG-EXT-12W-2L can withstand temperature variances ranging from 0° to 40°C and its low maintenance design offers up to ten years of operational life. An integrated pilot light indicates the presence of AC current and a test switch allows easy confirmation of proper emergency operation.

## Made in the USA Quality

- 1. No Maintenance Nickel-Cadmium Battery.
- 2. Copper Free Aluminum Alloy Construction.
- 3. Universal 120 through 277VAC Operation
- 4. 90 Minute Battery Backup Runtime.
- 5. Deep Discharge Battery Protection.
- 6. 1/2" NPT Conduit Hub.
- 7. Epoxy Powder Coat Finish.
- 8. 10 Year Rated Lifespan.
- 9. Fully Automatic Operation.
- 10. Solid State Internal Electronics.
- 11. Pilot Light AC Current Indicator.
- 12. Test Switch for Emergency Operation Confirmation.
- 13. Fully Electronic Circuit Control.

Specifications / Additional Information	
EXP-EMG-EXT-12W-2L	U.L Ratings
Lamp Type: LED	Class I, Division I & II, Groups B,C,D
Dimensions: 28.67"-H, 33.50"-W	Class II, Division I & II, Groups E,F,G
Watts: 12	Class III,
Materials: Copper Free Aluminum Housing	IP67 (water proof) rating
Voltage: 120/277VAC	UL 844
Lighting Configuration: Dual 6 Watt Bulbs	UL 924
Mounting: Wall Mount/Flat Surface Mount	NFPA101 (Life Safety Code)
Wiring: 1/2" NPT Threaded for Conduit	
U.L. Listing: U.S. Explosion Proof	
Battery Backup: High temp Nickel-Cadmium	Special Orders- Requirements
Battery Input Voltage: (Dual) 120/277VAC @ 60Hz	Contact us for special requirements
Unit Life Expectancy: 10 years	
Battery Backup Runtime: 90 Minutes	Toll Free: 1-800-369-6671
Battery Output Voltage: 12 VDC Nominal	Intl: 1-903-498-3363
Battery Output Current: 1000mA (Constant)	E-mail: sales@magnalight.com
Battery Output Power: 12 Watts (Max)	
Battery Operating Temp: 0 - 50C	
Battery Recharge Time: 24 hours from full discharge	
Scroll Down to Purchase-	

Part #: EXP-EMG-EXT-12W-2L (64186)

Larson Electronics LLCWWW.MAGNALIGHT.COM9419 E US HWY 175, Kemp, TX 75143Phone: 903.498.3363Fax: 903.498.3364Email: sales@magnalight.com





Page: 4



