



# Rubber Sheet Roll

## Technical Data Sheet

COLOR	BLACK
SURFACE	TEXTURED
TEMP RANGE	-10°F - 130°F
TENSILE	100 PSI
DUROMETER	50 SHORE A
ELONGATION	65%
FIRE RATED	NO
UV RATED	NO
CHEMICAL RESISTENT	MODERATE TO LOW
COMPOSITION	CRUMB RUBBER

### PSA DATA

THICKNESS	5 MIL
SURFACE	RELEASE LINER 1 SIDE
TEMPERATURE	250° F
COMPOSITION	ACRYLIC
FDA	NO

### Description

This Re-ground (crumb) rubber sheets have a unique texture and pliability suited for low cost applications. The reground rubber is a recycled crumb rubber that has an elongation of 65% which makes it most suitable for static applications. The material is pliable and versatile but is not recommended for high stretch or high use products.

Rubber Sheet Roll Shippensburg, PA 17257  
Phone: 866.832.6006

[info@rubbersheetroll.com](mailto:info@rubbersheetroll.com) [www.rubbersheetroll.com](http://www.rubbersheetroll.com)

REGROUND RUBBER

REGROUND RUBBER

All values given are averages based on test samples and the data given is based on what we have determined to be reliable. As results cannot be predicted or guaranteed for any specific set of conditions, each user should make their own determination of these products suitability for their particular application.