



# Rubber Sheet Roll

## Technical Data Sheet

COLOR	BLACK
SURFACE	SMOOTH
TEMP RANGE	- 30° F TO 220° F
TENSILE	1500 PSI
DUROMETER	70A NOMINAL
ELONGATION	175%
FIRE RATED	NO
UV RATED	MODERATE
CHEMICAL RESISTENT	MODERATE
COMPOSITION	SYNTHETIC

### PSA DATA

THICKNESS	5 MILS
SURFACE	RELEASE LINER ONE SIDE
TEMPERATURE	250° F
COMPOSITION	ACRYLIC
FDA	NO

### Description

Cloth Inserted Neoprene is a rubber that uses a cotton, one ply insert ideal for stress applications such as gasketing and diaphragms. Fabric inserted Neoprene rubber is well suited for applications requiring an extreme amount of tear strength, resilient rubber for outdoor and mechanical environments.

Fabric insert rubber is also used for conveyor belting and trailer / truck mud flaps.

**Rubber Sheet Roll Shippensburg, PA 17257**  
**Phone: 866.832.6006**  
**info@rubbersheetroll.com www.rubbersheetroll.com**

CLOTH INSERTED NEOPRENE

CLOTH INSERTED NEOPRENE

All values given are averages based on test samples and the data given is based on what we have determined to be reliable. As results cannot be predicted or guaranteed for any specific set of conditions, each user should make their own determination of these products suitability for their particular application. **Viton® is a registered trademark of DuPont Performance Elastomers.**