



**Medial View**  
showing flexible,  
breathable  
subshells

**CTi® OTS**

For the highest level of support and protection, the proven technology behind the classic CTi knee brace is available with off-the-shelf convenience. Outfitted with anatomically-correct Accutrac® hinges<sup>1</sup> and flexible cuffs<sup>2</sup> and buckles<sup>3</sup>, the rock-solid CTi carbon frame provides a rigid exoskeleton that stabilizes the knee joint. Breathable liners coated with bio-inert Össur® Sensil® Silicone<sup>4</sup> ensure CTi OTS remains properly positioned on the leg, for optimal functional benefit.



**INDICATIONS**

- ACL, MCL, LCL, PCL, rotary and combined instabilities
- All activity levels
- Standard model for medium to high impact levels
- Pro Sport model for highest impact levels

PART#	LEG	SIZE	MEASURING <sup>1</sup>
B-23X5Y0112	Right	Small	Caliper: 3.5-4"
B-23X6Y0112	Left	Small	Circumference: 11-12.625"
B-23X5Y0113	Right	Medium	Caliper: 4-4.5"
B-23X6Y0113	Left	Medium	Circumference: 12.625-14.25"
B-23X5Y0114	Right	Large	Caliper: 4.5-4.875"
B-23X6Y0114	Left	Large	Circumference: 14.25-15.375"
B-23X5Y0115	Right	XLarge	Caliper: 4.875-5.25"
B-23X6Y0115	Left	XLarge	Circumference: 15.375-16.625"
B-23X5Y0116	Right	XXLarge	Caliper: 5.25-75"
B-23X6Y0116	Left	XXLarge	Circumference: 16.625-18.125"

**X = 8** (Standard model) or **9** (Pro Sport model)  
**Y = 4** (PCL model) or **0** (not PCL model)

<sup>1</sup> Caliper: M/L at joint width in a standard, weight-bearing position  
Circumference: just below the distal border of the patella