

Cisco Networking Capabilities for Medianet

Product Overview

A medianet is an end-to-end architecture for a network comprising advanced, intelligent technologies and devices in a platform optimized for the delivery of rich-media experiences. A medianet has the following characteristics:

- Media-aware: Can detect and optimize different media and application types (telepresence, video surveillance, desktop collaboration, and streaming media) to deliver the best experience
- Endpoint-aware: Automatically detects and configures media endpoints
- Network-aware: Can detect and respond to changes in device, connection, and service availability

With the increasing adoption of new video and rich-media applications, medianet technologies become critically important to address challenges associated with the transmission of video, voice, and data over the network, including ensuring predictability, performance, quality, and security.

By accelerating deployment of applications, minimizing complexity and ongoing operational costs, increasing visibility into the network, and helping to scale the infrastructure for the best quality of experience (QoE), medianet technologies help address these challenges.

Capabilities and Benefits

Cisco® Networking Capabilities for Medianet extend the boundary of networks to the endpoints, creating tight integration between intelligent network services and the rich-media applications delivered over a variety of endpoints. Cisco endpoints are equipped with the **Media Services Interface (MSI)**, a software component that enables endpoints to consistently take advantage of intelligent network services to improve the quality of experience and reduce the cost of deployment and operations. MSI enables:

- The network to become media-aware so that the network can intelligently apply critical network services
- Rich-media applications to become network-aware, enabling them to dynamically adapt to network conditions and improve the range of troubleshooting options through tighter network integration

Cisco Networking Capabilities for Medianet provides capabilities across a range of network and endpoint devices to enable a medianet system to send, deliver, and optimize rich-media applications. Today's Cisco Networking Capabilities for Medianet focuses on reducing IT costs and the complexity of deploying video as well as improving the video experience. The capabilities also provide much improved visibility into the network to accelerate troubleshooting and the ability to assess the impact of voice, video, and data on the network.

Table 1 describes the capabilities, components, benefits, and features of Cisco Networking Capabilities 2.x for Medianet. The appendix discusses Cisco Networking Capabilities 1.0 for Medianet.

Table 1. Switches and Minimum Cisco IOS Software Release Requirements

| Capabilities | Benefit | Components and Features |
|---|--|--|
| Autoconfiguration of video endpoints | Helps simplify the deployment and reduce the ongoing operational costs of rich-media applications and endpoints | <ul style="list-style-type: none"> • Cisco IOS[®] Auto Smartports: Automates device configuration and registration to simplify management and equipment moves, adds, and changes; provides built-in recommended configurations for a variety of device types that are automatically applied when the device is plugged into the switchport • Cisco IOS Location: Automates physical location configuration and enables device asset tracking • Cisco AutoQoS: Simplifies access-switch quality-of-service (QoS) deployment • Media Services Interface (MSI): Residing on endpoints, enables autoconfiguration capabilities • Cisco Prime™ LAN Management Solution (Cisco Prime LMS): <ul style="list-style-type: none"> ◦ Offers a work center that simplifies the deployment of Cisco IOS Auto Smartports and facilitates the configuration of Cisco IOS Location settings to help enable and track medianet endpoints ◦ Performs an assessment of the network infrastructure to determine network readiness, including hardware, software, and performance capability based on Cisco Networking Capabilities 2.2 for Medianet recommendations; facilitates updates of device software to Cisco best practices recommendations. |
| Media monitoring | Enhances visibility into the network to simplify, generate baselines, and accelerate troubleshooting of video, voice, and data applications, and validates network capacity and configuration before deploying new applications or before events | <ul style="list-style-type: none"> • Cisco IOS Performance Monitor: Helps network operators quickly find and identify problems, including fault location, that impact the quality of video, voice, and data <ul style="list-style-type: none"> ◦ Provides performance statistics (packet loss, jitter, etc.) based on analysis of user traffic ◦ Allows creating application class-specific threshold crossing alerts ◦ Provides reporting through NetFlow export and MIB • Cisco IOS Mediatrace: Helps network operators understand the status and health of a network path by collecting critical information hop by hop, on specific media streams as they traverse the network <ul style="list-style-type: none"> ◦ Layer 2 and Layer 3 node discovery, with multiple profiles of information gathering ◦ Dynamic configuration of a granular performance monitor policy as well as data retrieval • Cisco IOS IPSLA Video Operation (Traffic Simulator): Helps network operators validate whether a network is ready for video and rich-media applications by stressing the network path with realistic, application-specific media streams <ul style="list-style-type: none"> ◦ Supports customized application profiles • MSI: Software component residing on endpoints, enables: <ul style="list-style-type: none"> ◦ Collection of network performance statistics (packet loss, jitter, etc.) ◦ Automatic triggering of a mediatrace for diagnostics upon detection of quality degradation by an endpoint • Cisco Prime Collaboration Manager (Cisco Prime CM): Simplifies operations of video collaboration services with end-to-end application and network visibility and identifies source of media service degradation and interruption from endpoints, video, and network infrastructure • Cisco Prime LMS Borderless Work Center for Medianet: Provides a dashboard for monitoring the status of medianet and visibility to all medianet endpoints, including where they are attached to the network |
| Auto-Registration of video endpoints | Automates the discovery of and registration to services available on the network. | <ul style="list-style-type: none"> • Auto-registration: Enables automated registration to services to automate endpoint/application deployment and configuration. |
| Media Awareness | Helps differentiate business critical applications for service assurance, consistency and optimal quality of user experience end-to-end. | <ul style="list-style-type: none"> • Flow Metadata: Manages and transfers application attributes to the network allowing appropriate policies to be applied at each hop, end to end • Media Services Proxy: Uses light weight deep packet inspection techniques to snoop standard based signaling protocols to produce flow metadata attributes that can then allow appropriate policies to be applied at each hop, end to end • Network Based Application Recognition 2 (NBAR2): Enables protocol detection for a network which is the process by which the system determines that a particular network flow is from a specific application. • Media Services Interface (MSI): Residing on endpoints, explicitly signals application context attributes (flow metadata) to the network |

System Requirements

Tables 2 and 3 list the switches and routers, respectively, and minimum Cisco IOS Software release requirements for each medianet capability. Table 4 lists the devices and requirements for the Cisco Media Services Interface.

The products and features listed in Tables 2 through 4 have been tested and documented to support reliable predictable customer deployments.

Table 2. Switches and Minimum Cisco IOS Software Release Requirements

| Platform | Minimum Cisco IOS Software Release | Package | Capabilities |
|---|------------------------------------|--------------------|---|
| Cisco Catalyst® 2960S and Catalyst 2960 Series Switches | 12.2(55) SE or later | LAN Base or higher | Autoconfiguration: <ul style="list-style-type: none"> • Auto Smartports • Location • AutoQoS |
| Cisco Catalyst 3750-X, 3750-E**, 3750G** and 3750V2 Series Switch | 12.2(55) SE or later | LAN Base or higher | Autoconfiguration: <ul style="list-style-type: none"> • Auto Smartports • Location • AutoQoS |
| | 12.2(58)SE2 or later | IP Base or higher | Media monitoring: <ul style="list-style-type: none"> • Performance Monitor • Mediatrace • IPSLA Video Operation—Sender and Responder |
| Cisco Catalyst 4500E Supervisor Engine 7-E and 7L-E | XE 3.3.0 SG or later | LAN Base or higher | Autoconfiguration: <ul style="list-style-type: none"> • Auto Smartports • Location |
| | XE 3.3.0SG or later | IP Base or higher | Media monitoring: <ul style="list-style-type: none"> • Performance Monitor • Mediatrace • IPSLA Video Operation—Sender and Responder* Media Awareness: <ul style="list-style-type: none"> • Flow Metadata • Media Services Proxy |
| Cisco Catalyst 4500E Supervisor Engine 6-E and Cisco Catalyst 4500 Supervisor Engine 6L-E | 12.2(54)SG1 | LAN Base or higher | Autoconfiguration: <ul style="list-style-type: none"> • Auto Smartports |
| | 15.1(1)SG or later | LAN Base or higher | Autoconfiguration: <ul style="list-style-type: none"> • Auto Smartports • Location |
| | 15.1.(1)SG or later | IP Base or higher | Media monitoring: <ul style="list-style-type: none"> • Performance Monitor • Mediatrace • IPSLA Video Operation—Responder Media Awareness: <ul style="list-style-type: none"> • Flow Metadata • Media Services Proxy |

| Platform | Minimum Cisco IOS Software Release | Package | Capabilities |
|--|------------------------------------|--------------------|--|
| Cisco Catalyst 4500X Series | XE 3.3.0 SG or later | IP Base or higher | Autoconfiguration: <ul style="list-style-type: none"> • Auto Smartports • Location Media monitoring: <ul style="list-style-type: none"> • Performance Monitor • Mediatrace • IPSLA Video Operation—Sender and Responder* Media Awareness: <ul style="list-style-type: none"> • Flow Metadata • Media Services Proxy |
| Cisco Catalyst 4900M, Catalyst 4948, Catalyst 4948-10GE, Catalyst 4948E, and Catalyst 4948E-F Switches | 12.2(54)SG1 | LAN Base or higher | Autoconfiguration: <ul style="list-style-type: none"> • Auto Smartports |
| | 15.1(1)SG or later | LAN Base or higher | Autoconfiguration: <ul style="list-style-type: none"> • Auto Smartports • Location |
| Cisco Catalyst 4900M, Catalyst 4948E, and Catalyst 4948E-F Switches | 15.1(1)SG or later | IP Base or higher | Media monitoring: <ul style="list-style-type: none"> • Performance Monitor • Mediatrace • IPSLA Video Operation—Responder |
| | 15.1(1)SG or later | LAN Base or Higher | Media Awareness: <ul style="list-style-type: none"> • Flow Metadata • Media Services Proxy |
| Cisco Catalyst 6500-E Series Switches Supervisor Engine 2T | 15.0(1)SY or later | IP Services | Media monitoring: <ul style="list-style-type: none"> • Performance Monitor • Mediatrace |

* Hardware accelerated

** End-of-Life announced on January, 31, 2012

Table 3. Routers and Minimum Release Requirements

| Platform | Switch Blade | Switch Image | Minimum Cisco IOS Software Release | Package | Capabilities |
|--|----------------|--------------|------------------------------------|---------|---|
| Cisco 3900 Series Integrated Services Routers (ISRs) | SM-D-ES3G-48-P | 12.2(55)EX | 15(0). 1M or later | - | Autoconfiguration: <ul style="list-style-type: none"> • Auto Smartports • Location • AutoQoS |
| | SM-D-ES3-48-P | | | | |
| | SM-ES3G-24-P | | | | |
| | SM-ES3-24-P | | | | |
| | SM-ES3G-16-P | | | | |
| | SM-ES3-16-P | | | | |
| Cisco 2900 Series ISRs Note: Cisco 1800 and 1900 Series and Cisco 2801 and 2901 ISRs do not support these switch blades.) | SM-ES3G-24-P | 12.2(55)EX | | | |
| | SM-ES3-24-P | | | | |
| | SM-ES3G-16-P | | | | |
| | SM-ES3-16-P | | | | |
| Cisco 3900 Series Integrated Services Routers (ISRs) | SM-D-ES3G-48-P | 12.2(58)SE2 | 15(0). 1M or later | - | Media monitoring: <ul style="list-style-type: none"> • IPSLA Video Operation—Sender and |
| | SM-D-ES3-48-P | | | | |
| | SM-ES3G-24-P | | | | |

| Platform | Switch Blade | Switch Image | Minimum Cisco IOS Software Release | Package | Capabilities |
|--|----------------|--------------|--|---|---|
| | SM-ES3-24-P | | | | Responder |
| | SM-ES3G-16-P | | | | |
| Cisco 2900 Series ISRs Note: Cisco 1800 and 1900 Series and Cisco 2801 and 2901 ISRs do not support these switch blades.) | SM-ES3-16-P | 12.2(58)SE2 | | | |
| | SM-ES3G-24-P | | | | |
| | SM-ES3-24-P | | | | |
| | SM-ES3G-16-P | | | | |
| | SM-ES3-16-P | | | | |
| Cisco 2900 and 3900 Series Integrated Services Routers | Not applicable | | 15.1(3)T or later | UC or Data | Media monitoring: <ul style="list-style-type: none"> • Performance Monitor • Mediatrace |
| | Not applicable | | 15.2(2)T | UC | Media monitoring: <ul style="list-style-type: none"> • IPSLA Video Operation—Sender (also requires PVD3 DSPs)* |
| | Not applicable | | 15.2(2)T | IP Base | Media monitoring: <ul style="list-style-type: none"> • IPSLA Video Operation – Responder |
| | Not applicable | | 15.2(1) T | Data | Media Awareness: <ul style="list-style-type: none"> • Flow Metadata |
| | Not applicable | | 15.2(3) T | Data | Media Awareness: <ul style="list-style-type: none"> • Media Services Proxy |
| Cisco 1900 Series Integrated Services Routers | Not applicable | | 15.1(3)T or later | Data | Media monitoring: <ul style="list-style-type: none"> • Performance Monitor • Mediatrace |
| | Not applicable | | 15.2(2)T | IP Base | Media monitoring: <ul style="list-style-type: none"> • IPSLA Video Operation – Responder |
| Cisco 880 and 890 Series Integrated Services Routers | Not applicable | | 15.1(3)T or later | Universal Image with Advanced IP feature license | Media monitoring: <ul style="list-style-type: none"> • Performance Monitor • Mediatrace |
| Cisco 890 Series Integrated Services Routers | Not applicable | | 15.2 (1) T | IP Base or higher | Media Awareness: <ul style="list-style-type: none"> • Flow Metadata |
| Cisco ASR 1000 Series Aggregation Services Routers | Not applicable | | Cisco IOS XE Software Release 3.5 or later | ASR 1001 Universal Image with Advanced IP feature license All other ASR 1000 series: Advanced Enterprise | Media monitoring: <ul style="list-style-type: none"> • Performance Monitor* • Mediatrace |
| | Not applicable | | Cisco IOS | ASR 1001 | Media Awareness: |

| Platform | Switch Blade | Switch Image | Minimum Cisco IOS Software Release | Package | Capabilities |
|----------|--------------|--------------|------------------------------------|--|-----------------|
| | | | XE 3.7 or later | Universal Image with Advanced IP feature license All other ASR 1000 series: Advanced Enterprise | • Flow Metadata |

* Hardware accelerated

Table 4. Devices and Requirements for Media Services Interface

| Devices and Products | Software Version | Capabilities |
|--|--|--|
| Cisco Digital Media Player 4310G | 5.2.2 or later | Location |
| Cisco Digital Media Player 4310G | 5.2.3 or later | Autoregistration |
| Cisco Digital Media Player 4400 | 5.2.3 or later | Autoregistration |
| Cisco Video Surveillance 4300 and 4500 Series IP Cameras | 2.0.0 | Auto Smartports |
| Cisco WebEx® meeting applications | WebEx Business Suite (WBS28) or higher | Media monitoring (Performance Monitoring) Media Awareness (Flow Metadata) |
| Cisco Jabber for Windows | UC 9.0(1) or later | Media Awareness (Flow Metadata) |

Management Solutions

Cisco Prime Assurance Manager

Cisco Prime Assurance Manager (AM) aggregates real-time information across multiple networks to deliver application-aware network performance visibility and troubleshooting. It helps network operators and engineers gain end-to-end visibility across architectures to facilitate the effective collection, analysis, and troubleshooting of performance, applications and end user experience over wired and wireless sessions.

The solution leverages many embedded technologies and standards such as NetFlow, Medianet Media Monitoring _ IOS Performance Monitor, SNMP to provide end-to-end application visibility, WAN optimization visibility, troubleshooting and Network readiness workflows while abstracting out a lot of the complexities involved in setting up the instrumentation. AM is also a multi NAM manager since it can centrally discover manage and get data from multiple NAMs in an enterprise network.

Features and Benefits:

- Service assurance: End-to-end visibility for applications, services, and end users
- Centralized performance monitoring: Performance data collected and aggregated from multiple sources
- Troubleshooting: Enhanced troubleshooting such as event triggers based on packet capture parameters
- Multi-NAM Management: Central discovery, configuration, reporting and troubleshooting leveraging multiple NAMs in the enterprise Network at various PINs.

For more details on Prime Assurance Manager, please visit www.cisco.com/go/pam

Cisco Prime Collaboration Manager

Cisco Prime Collaboration Manager (Cisco Prime CM) is a service and network management product specifically designed to support video collaboration (starting with Cisco TelePresence® conferencing in Release 1.0) over Borderless Networks (including medianets). It enables service and network operators to troubleshoot and correlate Cisco TelePresence service impairments end to end, including endpoint, infrastructure, and network problems.

The easy-to-use dashboards of the collaboration manager help IT operators:

- Efficiently manage large-scale service deployments and upgrade processes
- Significantly reduce operational costs of service monitoring and troubleshooting
- Gain detailed visibility into the media path and critical fault and performance statistics, with deeper visibility where a medianet is deployed
- Facilitate faster localization and resolution of service-affecting outages
- Provide immediate access to critical application usage and performance

These features help minimize service degradation and ensure user satisfaction.

For more information about Cisco Prime Collaboration Manager, please visit <http://www.cisco.com/go/cpcm>.

Cisco Prime LAN Management Solution

Cisco Prime LAN Management Solution (Cisco Prime LMS) is an integrated suite of management functions that simplify the configuration, administration, monitoring, and troubleshooting of Borderless Networks. The medianet Work Center provides day-1 through day-N workflows for assessing, preparing, and setting up autoconfiguration and location settings to aid the provisioning and tracking of medianet endpoints such as digital media players and IP video surveillance cameras. The medianet workflows enable the network operator to select the type of medianet to provision, and automatically prepare the network for deployment and check to ensure the appropriate location attributes are configured for tracking and monitoring purposes, reducing the chance for errors and time required to set up an end-to-end video infrastructure.

For more information about Cisco Prime LMS and the Medianet Work Center, please visit:

<http://www.cisco.com/go/lms>.

Enterprise Medianet Ecosystem Programs

The enterprise medianet ecosystem ensures interoperability among the network, applications, endpoints, and system management solutions, helping ensure business continuity and reduce IT costs while maximizing the user experience.

The Cisco Developer Network program for medianet systems management offers application programming interfaces (APIs) and documentation to enable network and application management vendors to support enterprise medianet features that offer customers a range of management and operation solutions. To learn more about the existing partner solutions for enterprise medianet, please visit

<http://developer.cisco.com/web/mnets/partners>

Services

Medianet Readiness Assessment Service

The Cisco Medianet Readiness Assessment Service (MRA) helps organizations ensure the successful implementation of rich-media applications and realize the full value of a video technology investment. The MRA assesses the readiness of the network based on a thorough analysis of the current infrastructure and the video and rich-media applications to be supported, and provides prepare and plan recommendations drawing from best practices.

For more information, please visit: <http://www.cisco.com/go/mra>.

For More Information

For more information about Cisco Networking Capabilities for Medianet, please visit: <http://www.cisco.com/go/medianet> or contact your local Cisco account representative.

Appendix: Cisco Networking Capabilities 1.0 for Medianet

The first step toward a medianet is a converged network for voice, video, and data. Cisco Networking Capabilities 1.0 for Medianet establishes a foundation for medianets. Recommendations for a foundation architecture are available in the Medianet Reference Guide:

http://www.cisco.com/en/US/docs/solutions/Enterprise/Video/Medianet_Ref_Gd/medianet_ref_gd.html.

Table 5 lists capabilities, features, and benefits of Cisco Networking Capabilities for 1.0 for Medianet.

Table 5. Capabilities, Features, and Benefits of Cisco Networking Capabilities 1.0 for Medianet

| Capabilities | Benefits | Features |
|--|--|---|
| Video-optimized technologies <ul style="list-style-type: none">• Cisco Performance Routing (PFR)• QoS• IP Multicast• Cisco Wide Area Application Services (WAAS) | Reduce traffic and server load and optimize the use of the network to achieve successful end-to-end video streaming. | <ul style="list-style-type: none">• Improve application performance and availability with Cisco Performance Routing by selecting the best path for each application based upon advanced criteria (delay, loss, jitter, etc.).• Maximize existing network resources with Cisco Performance Routing by using all possible paths without compromising performance.• Reduce traffic and server loads using IP Multicast to simultaneously deliver a single stream of information to thousands of users.• Deliver truly differentiated services for media applications using QoS.• Use WAN optimization technologies such as Cisco WAAS to improve performance and "reduce bandwidth footprint" of certain applications and create bandwidth media applications. |
| Visibility: <ul style="list-style-type: none">• Network-Based Application Recognition (NBAR)• NetFlow | Obtain end-to-end visibility to meet expanding and changing business needs. | <ul style="list-style-type: none">• Automatically discover media applications running on the network with NBAR so that appropriate network policies can be applied.• Achieve better visibility of the applications that are running on the network with NBAR and NetFlow integration to support business goals; for example, understanding the growth and patterns of network and media usage to allow for better planning and control of the network resources. |
| Extension of medianets to wired or wireless IP surveillance cameras: <ul style="list-style-type: none">• Cisco VideoStream | Extends IEEE 802.11n support to enable enterprise-class, wireless Cisco Video Surveillance IP Cameras and other live video streams | <ul style="list-style-type: none">• Includes Cisco Compatible Extensions to provide optimal network performance and video quality• Adds resilient wireless IP Multicast support to ensure reliable delivery of mission-critical live video stream traffic |

For information about each of the technologies, please visit the following links:

- Cisco Performance Routing (PfR):
http://www.cisco.com/en/US/partner/products/ps8787/products_ios_protocol_option_home.html
- Cisco Wide Area Application Services (WAAS):
<http://www.cisco.com/en/US/partner/products/ps6870/index.html>
- IP Multicast: http://www.cisco.com/en/US/partner/products/ps6552/products_ios_technology_home.html
- Quality of service (QoS):
http://www.cisco.com/en/US/partner/products/ps6558/products_ios_technology_home.html
- Network-Based Application Recognition (NBAR):
http://www.cisco.com/en/US/partner/products/ps6616/products_ios_protocol_group_home.html
- NetFlow: http://www.cisco.com/en/US/partner/products/ps6601/products_ios_protocol_group_home.html
- Cisco VideoStream:
http://www.cisco.com/en/US/partner/prod/collateral/wireless/ps6302/ps8322/ps10315/ps10325/white_paper_c11-577721.html



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)