

# QTERM®-A7





7" Widescreen HMI with Universal Connectivity and Choice of Programming Platforms

The QTERM®-A7 human machine interface features universal connectivity, a bright widescreen display and is UL listed Class I Div 2 and marine ABS certified. Industrially hardened, the QTERM-A7 can operate in -30 to 70 °C.



## Product Highlights

- ▶ 800 x 480 pixel WVGA, 7" (177 mm) diagonal, LED lighted, TFT color LCD display with touch screen
- ▶ -30 to 70 °C operating temperature
- ▶ UL listed Class 1 Div 2 and marine ABS certified
- ▶ NEMA-4X and IP66 sealing for harsh environments
- ▶ iX Software for automation control or Windows® Embedded CE 6.0 development



Dimensions shown in mm.

## QTERM-A7 Specifications

Feature	Detail	Description
Display	Type	800 x 480 WVGA, TFT color LCD
	Size	7" (177 mm) diagonal
	Lighting	LED
Touch Screen	Type	Analog-resistive with 4H hardness
Interface	Ethernet	10/100Base-T, RJ-45
	Serial	One EIA-232/422/485 DB9f; one EIA-232 DB9f
	USB	Two 2.0 full-speed host ports (Type A connectors)
Processor	Type	XScale™ PXA 300 ARM 624 MHz
Memory	RAM	128 MB
	Flash	4 GB
Realtime Clock	Standard	Battery-backed, 1 second resolution
Audio	Speaker	8 Ohms 0.7 Watts
Power	Input	10 to 32 VDC
	Consumption	7 Watts @ 24 VDC (typical), 11 Watts @ 24 VDC (max)
	PoE (optional)	8.5 Watts @ 48 VDC (typical), 12.2 Watts @ 48 VDC (max)
Mechanical	Type	Panel-mount
	Size	223 (W) x 153 (H) x 66 (D) mm
	Mass	1 kg
	Housing Material	Polymer

Environmental	Sealing - Front Panel	UL 50 Type 4X (outdoor), IP66, NEMA-4X
	Temperature	Operating: -30 to 70 °C; Storage: -40 to 85 °C
	Humidity	5 to 95%, non-condensing
	Vibration	4 g 10-1500 Hz
Certifications	Hazardous Locations	ANSI/ISA 12.12.01 (formerly UL 1604) Class I, Div 2
	UL	UL 508
	CE	EN55022, EN55024 and EN60950
	EMC	FCC Part 15
	Marine	ABS

Software	Operating System	Windows® Embedded CE 6.0
	Development Environments	Visual Studio®, iX Developer
	Development Languages	Visual Basic®, Visual C#®, Visual C++®, iX Software
	Runtime Environments	.NET Compact Framework, iX Runtime



### US Office

Beijer Electronics, Inc.  
 2212 South West Temple #50  
 Salt Lake City, Utah 84115-2648 USA  
[www.BeijerElectronicsInc.com](http://www.BeijerElectronicsInc.com) / 801-466-8770

### Headquarters

Beijer Electronics Products AB  
 P.O. Box 426  
 201 24 Malmö, Sweden  
[www.BeijerElectronics.com](http://www.BeijerElectronics.com) / +46 40 35 86 00

M01-039-00 REV 07  
 20 NOVEMBER 2012

Copyright © 2012 Beijer Electronics. All rights reserved.  
 The information at hand is provided as available at the time of printing.  
 Beijer Electronics reserves the right to change any information without  
 updating this publication. Beijer Electronics does not assume any  
 responsibility for any errors or omissions in this publication.