

The New Express Hot Air Roofing Tools

Given safety and strict building requirements, these products have been developed specifically for circumstances where an open flame is prohibited.

Express Sirocco: High-Output Detail Roofing Torch



APPLICATIONS:

Installation tool for hot air welded detail work for APP & SBS membrane systems

CHARACTERISTICS

Power Source	Propane with compressed air
Working Temp. (Max)	1832°F
Output @ 43.5 PSI	40,500 BTU
Propane Consumption @ 43.5 PSI	2.17 lbs/hr
Size	18.0 x 8.25"
Weight	2.2 lbs (not including hose)
Warranty	1 year warranty included



COMPONENTS:

Kit includes 40,500 BTU Hot Air Tool, Duplex hose, Duplex regulator, Titanium tip all packed in an Express carrying case

Additional benefits include:

- The power of gas, but the safety of hot air.
- Easy, lightweight and safe to handle.
- Sturdy tools that can handle anything on the roof.

Express Vulcane: Dual Output Detail Roofing Torch



APPLICATIONS:

Premium, dual purpose repair tool for hot air welded TPO & PVC systems and open flame repairs for APP & SBS membrane systems

CHARACTERISTICS

Power Source	14.1 oz MapPro cylinder
Working Temp. (Max)	1049 °F
Output	Hot air: 1260 W to 2740 W Open flame: 17,250 BTU
Gas Consumption	Hot air: 0.21 lbs/hr to 0.45 lbs/hr Open flame: 0.75 lbs/hr
Size	11.8 x 9.06"
Weight	3.85 lbs (with canister)
Warranty	1 year warranty included



COMPONENTS:

Kit includes the Vulcane Pistol Grip, 1.9lb Gas cylinder, Hose adapter, 2 Hot air burners, 1 5kW Open flame burner in an Express carrying case.



Express Heating Gun: Premium Self-Contained Hot Air Torch



APPLICATIONS:

Cordless propane fired hot air tool for flashing and repairs of single-ply and self-adhered asphalt membrane systems

CHARACTERISTICS

Power Source	Propane canister
Working Temp. (Max)	932 °F
Output	500 W
Gas Consumption	0.08 lbs/hr
Size	6.5 x 10.6"
Weight	1.37 lbs (with canister)
Warranty	1 year warranty included



COMPONENTS:

Kit includes the 4600 Heating Gun, 2 - 445 Propane canisters, Flat tip in an Express carrying case.