

For every environment of your life.





2420 Grenoble Road Richmond, Virginia 23294 Tel. 800.782.5742

QUIETGLUE PRO



TECHNICAL CHARACTERISTICS

Sizing

28 oz. Tubes (Minimum 12) 5 Gallon Bucket Orange

Color

FEATURES

- Proven Highest Noise-Reducing Performance Compared to Other Noiseproofing Compounds
- Easy toUse
- Does Not Require Special Training
- Low VOC, Water-Based Compound, Solvent-Free
- Lab Tested in Accordance with ASTM D3273 and E90
- Greener Product Certification
- Density 1.030 kg/m3
- Viscoasity 1,000,000 1,500,000 Centipoise
- Drying Time 1-2 Hours
- Coverage 16 sqft/tube, 73 sqft/gallon
- Storage Temp 40° F 100° F (Do Not Freeze)
- Cut the Drywall to Spec
- Apply QuietGlue Pro with any Standard Caulking Gun
- Screw into Existing Wall or New Drywall and Enjoy!

APPLICATONS

- Residential
- Renovations
- Home Theaters
- Curved Walls

Call for quantity discounts

DESCRIPTION

QuietGlue Pro is the highest performing, lowest cost soundproofing compound on the market, designed to be very cost effective for do-it-yourself projects. QuietGlue Pro damping compound is fast, easy to use, and it works.

QuietGlue Pro FAQ

What is QuietGlue Pro?

QuietGlue Pro is a soundproofing glue which is applied between two rigid materials. (i.e. two layers of regular drywall)

What is QuietGlue Pro used for?

It is used to adhere two rigid materials together creating a high performance noise reducing partition in new and existing construction (walls, ceilings, floors). Like any other sound damping glue product, QuietGlue Pro is most suitable for DIY or small projects.

How does QuietGlue Pro work?

QuietGlue Pro is applied in between two rigid layers (wall or partition). When noise passes through a wall or partition the Quiet Glue Pro coverts the sound vibration into a thermal energy, which cannot be heard.

How do I use QuietGlue Pro?

QuietGlue Pro is designed for small DIY construction.

Do I need screws when laminating with QuietGlue Pro?

Yes, fasteners are required. Since QuietGlue Pro is not a structural adhesive; the drywall must be screwed appropriately to the framing members.

What is the coverage?Tubes:

Two 29 oz. tubes per 4'X8' sheet 1 Gallon: 73 sqft/gallon

What is the difference between QuietGlue Pro and Green Glue?

QuietGlue Pro performs better then Green Glue and cost 32% less!