



Specifications	
Media Type	MIL, ISO, and DIN Silver aperture cards
Film Types	Silver and Diazo
Card Generation	Odd or Even
Reduction Ratios	7.5x to 40x (variable)
Card Input	Single Card
Hollerith Reading	Not Applicable
Image Processing System	SMARTCODE
Printing Software	Demand Microfilm Print (DMP)
Display	2 modes with zoom and pan
Drawing Sizes	May be user defined within limits of A to E and Ao to A4
Scaling Accuracy	±0.5%
Resolution	100-400 dpi
Scan Speed	10 seconds per scan
File Format Output	Bitonal: TIFF, CALS, PNG, PDF Greyscale: JPEG, BMP, RAW TIFF, PNG, PDF
Production Tools	Manual Rotation, Manual Cropping, Manual Deskew, Viewing Facility, Logging File Capability, Framing with Rescan, Framing without Rescan, Reprocess, Check Print Capability, Print Enlarged
Safety	CE, TUV, UL, FCC, CUL
Customer Support	Smart Assist WebEx Online Training and Product Support
Operating System	Windows® 7 Professional (32 or 64 bit); Downgrade to Windows® XP Available

Installation Specifications	
Weight	Net: 4.8 lb. (2.2 kg) Shipping: 9.8 lb. (4.5 kg)
Dimensions	5.75" w x 7.75" d x 3.75" h 146 mm x 197 mm x 95 mm
Shipping Dimensions	11.25" w x 18.25" d x 7.5" h 285.75 mm x 463.6 mm x 190.5 mm
Power Requirement	110-240 Vac, 50/60 Hz, 1.7 Amps
Electrical Cord	USA IEC320-C13 to NEMA 5-15P Other IEC320-C13 to Local Plug
Environment	60°F to 80°F (15°C to 27°C) 40% to 60% R.H. Non-condensing

