



WAKE FLAME SL



SURFACE




STEALTH



Wake Flame SL lights are available in either surface mount, that screw from the front, or stealth mount that comes with a 2.5" stud that is designed for a 2" thick or less transom. Studs can be replaced with longer studs for thicker transom's.

Rigid Industries is proud to introduce the newest addition to the Marine Series, the Wake Flame SL underwater light. The Wake Flame SL utilizes an incredible Triplex® coating process that is up to 5 times stronger than MIL-A-8625 (Military spec for anodic coatings). This process safely allows for the use of aluminum in salt water environments. Works with or without DMX controllers as well as with multiple lights. Limited lifetime warranty.

- Produces up to 4500 Lumens
- Runs on 12-28V DC
- EN 55015:2006 EMC Complaint
- MIL810-STDG Vibration Certified
- ROHS Compliant
- Over / Under Voltage Protection
- Operating Temp -40° F ~ +145° F
- 50,000+ Hour Lifespan
- Protected Against RFI / EMI
- Instant On / Off
- Scratch Resistant Lens Coating
- 9' Marine Rated Connection Wire



SPECIFICATIONS

Product Description	Part #	Min/Max Voltage	AMP Draw	LEDs	Fixed Lumens*
Wake Flame SL Surface Mount - White	89211	12 - 28V	3	9	4500
Wake Flame SL Stealth Mount - White	89221	12 - 28V	3	9	4500
Wake Flame SL Surface Mount - Blue	89212	12 - 28V	2.3	9	810
Wake Flame SL Stealth Mount - Blue	89222	12 - 28V	2.3	9	810
Wake Flame SL Surface Mount - Green	89213	12 - 28V	2.3	9	1260
Wake Flame SL Stealth Mount - Green	89223	12 - 28V	2.3	9	1260

* Based on LED manufacturer specifications