



# Heated Backup Camera System With Color 7" WATERPROOF Multi-View LCD Monitor

for Open & Harsh Cab Environments









- 7" Waterproof Monitor With Membrane Touchpad
- High Resolution With Ultra Sharp DIGITAL Display & LED-Backlit Panel
- Multi-View LCD Monitor Can Accept Up To 4 Camera Inputs
- Heavy Duty, Heated Camera Provides 120° Field Of Vision
- 6 InfraRed LED's in Camera Provide Up To 30 Ft. of Night Time Visibility
- Integrated Audio Built-In Camera Mic & Powerful Monitor Speakers
- Versatile Mounting On Dashboard, Windshield or Overhead Location
- Two Year Warranty Included







## A Century of Automotive Vision Safety

#### **MULTI-VIEW WATERPROOF MONITOR P/N: STSM207 (Included In Kit)**

Screen Size (Diagonal)

Maximum No. of Cameras 4 Inputs/Channels

**Screen Ratio** 16:9 **Contrast Ratio** 300:1 Video System **NTSC** Voltage Input 12~24 Vdc

Operating Temperature °F (C°) -22° to 158° (-30° to +70°) Storage Temperature °F (C°) -40° to 176° (-40° to +80°)

**Dust\Water Rating** IP67 **Shock Rating** 100q **Vibration Rating** 15g **Speaker Impedance** 8 Ohms Weight 1.5 lbs. 7" x 5.75" x 1" Dimensions W x H x D Sun Shade Included 400 cd/m2 **Brightness** 

**Monitor Mounting Options** Versatile Duckfoot & U-Bracket



#### **HEATED CAMERA P/N: STSC107 (Included In Kit)**

**Image Device** 1/3" CCD **Pixels** 250,000 TV Lines 380

InfraRed LED's 6 High-Output

0 LUX (Infrared LED's on) Minimum Illumination

**Night Vision Range** 30 Feet

**Video Output** 1.0 Vp-p, 75 Ohm

Dust\Water Rating IP67 **Shock Rating** 100G **Vibration Rating** 15G Field of View 120°

Operating Temperature °F (°C) -22° to 158° (-30° to +70°) Storage Temperature °F (°C) -40° to 176° (-40° to +80°)

Weight .5 lb.

2.5" x 1.7" x 2.5" Dimensions W x H x D

Audio Yes

Construction Cast Aluminum Housing

w/ Stainless Steel Mounting Bracket & Weather Shield



STSC 107 Standard Camera (included in kit)



STSC117 Vertical Tilt Camera (camera lens automatically pivots up/down w/ trigger inputs)



STSC127 Shutter Camera (camera lens is protected by automatic lens cover)



Side Mount Camera (universal left or right side mount camera)

### HARNESS P/N: STSH307 (Included In Kit)

60' Heavy Duty w/ Twist - Lock Connectors

#### **Optional Harnesses:**

STSH308 - 16.5' Harness

**STSH310** - 60' Harness Extension (used with STSH308)

STSH306 - 60' Harness (for STSC117 Only)



**STSH307** Standard Harness

#### **Optional Harnesses:**







**STSH310** 





