

55" Multi-Touch Display

Retail Hospitality Medical Restaurant/QSR

V5580I-U2 V5580I-U2x2

Large-Format Display Infra Red

At a Glance

- Commercial grade design
- LED backlit
- Landscape or portrait orientation
- Built-in speakers
- Entry-level touch solution

Applications

- Retail
- Hospitality
- Medical
- Restaurants

Contact Us

220 Tradesmen Dr. Hutto, Texas 78634 1.800.320.5944 sales@touchsystems.com www.touchsystems.com The V 55" large-format display is one of TouchSystems' more budget-conscious displays, but the price tag is perfect for the person entering the touch technology arena. The display is LCD and LED-backlit, ensuring crisp images and brilliant colors. The LED backlighting reduces energy consumption and results in a slimmer depth. The display is integrated with infra red, a technology that allows for pinch to zoom and gestures, and is **Windows 8 ready**. It also is offered as a dual-touch (V5580I-U2x2) solution.



V5580I-U2

Specifications

Viewable Image Size	55"
Touch Technology	Infra Red (Multi-Touch)
Pixel Pitch	0.63 mm
Brightness	320 cd/m^2
Contrast Ratio	4000:1
Aspect Ratio	16:9
Resolution	1920 x 1080
Response Time	8 ms
Viewing Angle	178° Vertical, 178° Horizontal
Synchronization	31.5-91.1 kHz (Horizontal); 50-85 Hz (Vertical)
Compatibility	PC and Mac
Connectivity	DisplayPort, HDMI, DVI-D, VGA 15-pin D-sub, 5 BNC, BNC Composite, S-Video, RCA Audio, Stereo Mini-Jack (2), HDMI Audio, DisplayPort Audio, RS-232C, Ethernet (RJ45), IR Remote, DDC/CI
Connectivity Power Consumption	5 BNC, BNC Composite, S-Video, RCA Audio, Stereo Mini-Jack (2), HDMI Audio, DisplayPort Audio, RS-232C, Ethernet (RJ45), IR Remote,
·	5 BNC, BNC Composite, S-Video, RCA Audio, Stereo Mini-Jack (2), HDMI Audio, DisplayPort Audio, RS-232C, Ethernet (RJ45), IR Remote, DDC/CI
Power Consumption	5 BNC, BNC Composite, S-Video, RCA Audio, Stereo Mini-Jack (2), HDMI Audio, DisplayPort Audio, RS-232C, Ethernet (RJ45), IR Remote, DDC/CI On: 100W; Standby: <2W
Power Consumption Operating Temperature	5 BNC, BNC Composite, S-Video, RCA Audio, Stereo Mini-Jack (2), HDMI Audio, DisplayPort Audio, RS-232C, Ethernet (RJ45), IR Remote, DDC/CI On: 100W; Standby: <2W 5-40° C
Power Consumption Operating Temperature Operating Humidity	5 BNC, BNC Composite, S-Video, RCA Audio, Stereo Mini-Jack (2), HDMI Audio, DisplayPort Audio, RS-232C, Ethernet (RJ45), IR Remote, DDC/CI On: 100W; Standby: <2W 5-40° C 20-80%
Power Consumption Operating Temperature Operating Humidity Dimensions (WxHxD)	5 BNC, BNC Composite, S-Video, RCA Audio, Stereo Mini-Jack (2), HDMI Audio, DisplayPort Audio, RS-232C, Ethernet (RJ45), IR Remote, DDC/CI On: 100W; Standby: <2W 5-40° C 20-80% 50.240 x 29.19 x 3 in (without stand) - IR



V55 55" Multi-Touch Display

Retail Hospitality

Medical

Corporate

V5580I-U2 V5580I-U2x2

Large-Format Display Infra Red

At a Glance

- Commercial grade design
- LED backlit
- Landscape or portrait orientation
- Built-in speakers
- Entry-level touch solution

Applications

- Retail
- Hospitality
- Medical
- Restaurants

Contact Us

220 Tradesmen Dr. Hutto, Texas 78634 1.800.320.5944 sales@touchsystems.com www.touchsystems.com







