## TPC WIRE & CABLE CORP.

# NEW PRODUCTS

## Thermo-Trex<sup>®</sup> Silica Ultra-Sleeve<sup>™</sup> High Temperature Sleeving

- Continuous Operating Temperature: 1800°F (982°C)
- Max Short Term Exposure: 3000°F (1650°C)
- Flame Resistance: Outstanding
- Weld splatter resistance: Excellent

- Molten splash resistance: Good
- Flexibility: Outstanding
- Abrasion resistance: Moderate
- Water and oil resistance: Moderate

Thermo-Trex® Silica Ultra-Sleeve™ is a braided silica fiber that is 96% pure. Silica offers temperature resistance up to 3,000°F (1,650°C) while offering outstanding flame resistance, flexibility and tensile strength. It also doesn't have the negative health effects associated with asbestos or ceramic sleeves. Additional inside diameters up to 4 inches are available upon request. This silica material can be used to create a custom blanket for a specific piece of equipment or cabinet as well.



### **APPLICATIONS**

- Steel Mills
- Manufacturing Plants
- Foundries

- Glass Factories
- Welding & Cutting Shops

### ORDERING INFORMATION (Call for pricing & availability)

PART NO.	SLEEVING INNER DIAMETER (IN.)*
49900	0.25
49901	0.50
49902	1.00
49903	1.50

\*Additional inside diameters up to 4" are available upon request.



**TPC WIRE & CABLE CORP.** HEADQUARTERS 9600 VALLEY VIEW RD, MACEDONIA, OHIO 44056 USA 800-521-7935 • FAX 866-528-2930 • CANADA 800-545-0122 • MEXICO 001-877-283-1696 CHILE 1230-020-0229 • COLOMBIA 0-1-800-915-7519 • PERU 0800-54863 • **WWW.TPCWIRE.COM** 

WARRANTY AND DISCLAIMER: Seller makes no warranties, express or implied, with respect to this product, and seller disclaims any implied warranties of merchantability or fitness for any particular purpose. Further, seller will not be responsible for any consequential, incidental or indirect damages (including, but not limited to, any loss of profit) from any cause whatsoever.

