

Roof Sealing Paint

Description

Twistfix Roof Sealing Paint is a UV stable, multi-purpose liquid roof membrane. A solvent based acrylic coating with fibre reinforcement pre-dispersed in the can. Ideal for permanent and emergency repairs.

Surface Preparation:

Surface must be sound and free of friable materials, oil and grease.

To obtain the best result remove all surface debris and surface water using a stiff broom and power wash.

Repairs to cracks/holes up to 10mm without any scrim. Fungus, mould and lichens must be removed prior to coating. Additional protection against fungal spores can be achieved by pre-treating with a moss remover.

Existing coatings must be inspected and adhesion tests carried out prior to application.

Waterproofing for:

Flat and Pitched Roofs, Corrugated Asbestos, Roof Lights, Flashings, Roofing Felt, Gutters, Slate, Asphalt, Lead, Glasshouses, Metal and Fibreglass.

Colour:	Grey
Coverage Rates:	1 - 2kg per m ² on average.
Drying Time:	Up to 72 hours dependent on the ambient Temperature.
External use only.	Container Sizes: 5 kg.
Shelf Life:	12 months
Flash Point:	40°C
Storage:	Store away from children, preferably under cover and between 5°C - 20°C.



Application

Roof Sealing Paint is easily applied using a brush or roller.

Treat all details first. In areas where excessive movement may occur additional reinforcement can be incorporated into the coating.

Roof Sealing Paint can be applied in one coat, but experience has shown that a two coat application ensures a greater uniformity of coating thickness.

Roof Sealing Paint requires no primer on most surfaces. It is however good practice to carry out adhesion tests prior to application of the coating.

Roof Sealing Paint will tolerate damp surfaces and in an emergency can be used in the rain. For best results however apply to a dry surface.

Application temperature should be between 5°C and 25°C.
EXTERNAL USE ONLY.

Health & Safety: Please refer to health and safety data sheet on Roof Sealing Paint.

Further Information: In the event of further queries or problems concerning the use of this product, please contact Twistfix.

Twistfix Ltd
6th Floor, 8 Exchange Quay, Manchester M5 3EJ
81 Oxford Street, London W1D 2EU

www.twistfix.co.uk

© Twistfix Ltd 2012 Doc RSP v1201

technical helpline

0845 123 6006

sales line

0845 123 6007