

Midbrook Medical's ultrasonic cleaning systems offer a full range of features providing the most advanced systems available anywhere. These powerful units incorporate 316L, 14 and 12 gauge stainless steel tanks and stainless steel skirts for long term reliable performance. They provide the cleaning power and performance that medical facilities and laboratories expect in a precision ultrasonic cleaning system. Combined with Midbrook's patented transducers and patented high performance 5300 series generators, they are the largest and most powerful portable console and bench top systems in the industry.



Model 3900

- Ultrasonic cleaning equipment designed for ultimate performance
- Engineered and built for high power, efficiency, and reliability
- All stainless steel for a lifetime of problem free service
- Self-contained, compact, and portable
- Patented transducer technology
- Simultaneous multi-frequency for enhanced performance
- Patented generators with variable up-sweep circuitry to eliminate hot spots and dead
 zones
- Backed by Midbrook Medical's industry leading warranty and service
- Made in the USA





STANDARD FEATURES:

- All stainless steel construction
- 316L stainless steel tanks
- TIG welded inside and out for long-term reliability
- High power 40kHz transducers
- Simultaneous Multi-frequency
- Powered by patented 5300 series generators
- Intensity Control (Model 3900)
- Thermostatically controlled heat
- Low liquid level heater protection
- Drain with valve
- Cycle timer (Model 3900)
- Industry leading warranty and service
- Circuitry-4kHz variable sweep eliminates "hot spots" and "dead zones"

OPTIONS:

- Stainless steel basket
- Stainless steel lid
- Intensity control (Model 400, 900, 1500)
- Overflow plumbing
- Cycle timer (Model 400, 900, 1500)
- Custom sizes
- 120V or 240V
- Cleaning detergents
- CE certification
- TUV (UL/CSA) certification

Tank Model Number	Inside Dimensions W x L x D	Overall Dimensions W x L x H	Liquid Capacity	Ultrasonic Power (Pk/Avg Watts)	Amount of Heat (Watts)	Input Voltage (50/60Hz)
Model 400 4-Gallon	12 x 8 x 10 " 305 x 203 x 254 mm	16 x 18 x 16 " 406 x 457 x 413 mm	4 Gallon 15 Liters	500/250	500	120V
Model 900 9-Gallon	8 x 22 x 12 " 203 559 x 305 mm	18 x 26 x 17 " 457 x 660 x 432 mm	9 Gallon 34 Liters	500/250	500	120V
Model 1500 15-Gallon	14 x 20 x 14 " 356 x 508 356 mm	24 x 24 x 20.25 " 610 x 610 x 514 mm	15 Gallons 57 Liters	1000/500	1000	120V
Model 3900 39-Gallon	18 x 32 x 16 " 457 x 813 x 406 mm	23 x 41 x 39 " 584 x 1041 x 991 mm	39 Gallons 148 Liters	3000/1500	2000	240V

