

# PM-S 0057

## 5.7" 640 x 480 TFT LCD Open Frame LCD Monitor Wide Working Temperature



### » Specifications

**Material:**

Heavy-duty steel

**LCD Panel:**

Size: 5.7"

Max. Resolution: 640 x 480

Brightness: 400 cd/m<sup>2</sup>

Contrast Ratio: 800:1

Viewing Angle (H/V): 160'(H)/ 140'(V)

Active Area (mm): 115.2 x 86.4

MTBF: 35,000 hrs

Backlight: LED

Colors: 262K

Signal Input: VGA

Optional 700 / 1000 nits high brightness panel

Option digital signage (stand alone), MP 480P

Optional light sensor or motion sensor

**Video input:**

VGA video input

Option for DVI or SV + AV

**Touch Screen (Option):**

Resistive or Capacitive type touchscreen monitor

USB port

**Rear panel control:**

power on/off switch

OSD membrane switch

**Mounting Type:**

Open frame monitor with front mounting bracket

VESA (75mm) mounting holes

**Protection:**

Protected glass (AR/AR with anti-vandal/AG)

**Power Supply:**

External Auto-sensing 90~260VAC, 50/60Hz power adapter

Option for 24 VDC power supply

### » Features

- » Open frame monitor with front mounting bracket
- » 5.7 inch 640 x 480 LED backlight monitor
- » 400-nits high brightness LCD panel
- » -30°C to 80°C wide range working temperature
- » VGA video input, option for DVI / SV + AV
- » Option for touch screen monitor
- » Option for light or motion sensor
- » Option for 700/ 1000 nits high brightness panel
- » Wall/ panel/ VESA (75mm) mount ready
- » External AC adapter. Option for 24VDC power input

**Connectors:**

1 x VGA port (15 pin female D-Sub)

1 x PC Audio (stereo headphone jack)

1 x DC power plug

**Audio System:**

2W speaker x 2

**Weight:**

6.61lbs

**Dimension:**

6.18"(W) x 5.59"(H) x 2.17"(D)

**Certification:**

FCC, CE

**Environmental:**

Operating: -30°C to 80°C (22°F to 176°F)

Storage: -30°C to 80°C (22°F to 176°F)

Relative humidity: 10~90%, non-condensing

### » Ordering Guide

**PM-S0057:**

5.7 inch 640 x 480 400-nit brightness industrial monitor & open frame monitor, VGA video input, black color.

VGA video input, Option for touch screen, DVI / SV + AV, high brightness panel, motion sensor, light sensor, digital signage (stand alone) & DC power supply.

## ACNODES

14628 Central Ave.  
Chino, CA91710  
tel: 909.597.7588, fax: 909.597.1939

© Copyright 2014 Acnodes, Inc.  
All rights reserved. Product description and product specifications are subject to change without notice. For latest product information, please visit Acnodes' web site at [www.acnodes.com](http://www.acnodes.com).