

# PM-S 0150

## 15" 1024 x 768 TFT LCD Open Frame LCD Monitor Wide Working Temperature



### » Specifications

**Material:**

Heavy-duty steel

**LCD Panel:**

Size: 15"

Max. Resolution: 1024 x 768

Brightness: 350 cd/m<sup>2</sup>

Contrast Ratio: 1500:1

Viewing Angle (H/V): 170'(H)/ 170'(V)

Active Area (mm): 304.13 x 228.10

MTBF: 35,000 hrs

Backlight: LED

Colors: 16.2M

Signal Input: VGA

Optional 700 / 1000 / 1500 nits high brightness panel

Option digital signage (stand alone), MP 480P/1080P

Optional light sensor or motion sensor

**Video input:**

VGA video input

Option for DVI or DVI + HDMI or SV + AV

**Touch Screen (Option):**

Resistive, Capacitive or SAW type touchscreen monitor

USB port

**Rear panel control:**

power on/off switch

OSD membrane switch

**Mounting Type:**

Open frame monitor with front mounting bracket

VESA (75mm) mounting holes

**Protection:**

Protected glass (AR/AR with anti-vandal/AG)

**Power Supply:**

External Auto-sensing 90~260VAC, 50/60Hz power adapter

Option for 24 VDC power supply

### » Features

- » Open frame monitor with front mounting bracket
- » 15 inch 1024 x 768 LED backlight monitor
- » 350-nits high brightness LCD panel
- » -15°C to 65°C wide range working temperature
- » VGA video input, option for DVI / DVI + HDMI / SV + AV
- » Option for touch screen monitor
- » Option for light or motion sensor
- » Option for 700/ 1000/ 1500 nits high brightness panel
- » Wall/ panel/ VESA (75mm) mount ready
- » External AC adapter. Option for 24VDC power input

**Connectors:**

1 x VGA port (15 pin female D-Sub)

1 x PC Audio (stereo headphone jack)

1 x DC power plug

**Audio System:**

2W speaker x 2

**Weight:**

11.02lbs

**Dimension:**

13.59"(W) x 11.77"(H) x 2.28"(D)

**Certification:**

FCC, CE

**Environmental:**

Operating: -15°C to 65°C (5°F to 149°F)

Storage: -30°C to 80°C (22°F to 176°F)

Relative humidity: 10~90%, non-condensing

### » Ordering Guide

**PM-S0150:**

15 inch 1024 x 768 350-nit brightness industrial monitor & open frame monitor, VGA video input, black color.

VGA video input, Option for touch screen, DVI / DVI + HDMI / SV + AV, high brightness panel, motion sensor, light sensor, digital signage (stand alone) & DC power supply.

## ACNODES

14628 Central Ave.  
Chino, CA91710  
tel: 909.597.7588, fax: 909.597.1939

© Copyright 2014 Acnodes, Inc.  
All rights reserved. Product description and product specifications are subject to change without notice. For latest product information, please visit Acnodes' web site at [www.acnodes.com](http://www.acnodes.com).