

# RMC 5025

**1U 9.8" Depth Rackmount Computer**  
**Core i5-3230M Dual-Core 2.6GHz CPU**  
**2 or 6 Gigabit LAN ports**



## » Features

- » 1U High Rackmount Computer
- » 9.8 inch short depth chassis
- » Core i5-3230M Dual Core 2.6GHz processor
- » 2 x 2.5" internal drive bays
- » 2 x Gigabit Ethernet LANs port (option for 6 ports)
- » 4 x USB ports & VGA + HDMI+ DisplayPort video ports
- » 2 x mini PCIe expansion slots (option for 1 x PCI slot)
- » 250W 80+ Bronze level power supply

## » Specifications

### Construction:

Heavy-duty steel cold-rolled steel

### Embedded System:

Form Factor: 1U Rackmount

Motherboard: Mini-ITX

CPU Type: Core i5 3230M Dual-Core 2.6GHz

Memory: 2 x 240 pin DDR3 SODIMM sockets, max. 16GB

SATA: 2 x SATA ports (6Gbps) & 4 x SATA II ports (3Gbps)

2 x 2.5" internal drive bays

2 x Gigabit Ethernet RJ-45 LAN ports, option for 6 ports

Audio: Realtek ALC662 CODEC

4 x USB ports

### Chipset:

QM77 Express

### I/O layout:

2 x RJ45 LAN ports, Option for 6 x RJ45 LAN ports

2 x USB 3.0

1 x VGA

1 x HDMI

1 x DisplayPort

1 x RS-232 serial port

2 x USB 2.0

3 x Audio I/O

### Storage device:

2 x 2.5" Internal Drives

### System LED Indicator:

Power on/off button

System Reset button

Status LEDs (Power, HDD, NIC)

### Expansion slot:

1 x full size mini PCIe expansion slot

1 x half size mini PCIe expansion slot

Option for 1 x PCI expansion slot

### Cooling Fan:

Supports up to 2 x 40mm case fans

### Power supply:

250W Enhance ENP-7025B 80+ Bronze 1U PSU

MTBF 100,000 hrs

Universal AC (90~264 VAC @ 47~63Hz)

### Dimension:

17"(W) x 9.8 "(H) x 1.74"(D)

### Environmental:

Operating Temperature: 0°C ~ 50°C

Non-operating Temperature: -20°C to 70°C

Humidity: 8~90%, non-condensing

## » Ordering Guide

### RMC 5025:

Rack mount computer, Core i5-3230M 2.6GHz dual core embedded computer, up to 16GB DDR3 SODIMM memory, Mini-ITX M/B, 2 x mini PCIe expansion slot. 1U high and 9.8 inch depth rack mount chassis. Option for 1 x PCI expansion slot.



14628 Central Ave,  
Chino, CA 91710  
tel: 909.597.7588,  
fax: 909.597.1939

© Copyright 2014 Acnodes, Inc.

All rights reserved. Product description and product specifications are subject to change without notice. For latest product information, please visit Acnodes' web site at [www.acnodes.com](http://www.acnodes.com).