

# LED

## Versa Bar

### Extra Long Run

### Warm White

### Dimmable



Clips Included

VERSAS BAR XLR  
CLEAR LENS



“Connect even more Versa Bars together without voltage drop”

• QUICK MOUNT MAGNETS MOUNTED INTO THE BACK OF BAR

CLEAR MODELS     VSCXLR10WW24V     VSCXLR20WW24V     VSCXLR30WW24V     VSCXLR40WW24V     VSCXLR70WW24V

FROSTED MODELS     VSFXLR10WW24V     VSFXLR20WW24V     VSFXLR30WW24V     VSFXLR40WW24V     VSFXLR70WW24V

COLOR; warm white	3000K	3000K	3000K	3000K	3000K
XLR LENGTH	10.39"	20.24"	30.08"	39.92"	69.48"
LUMEN OUTPUT (clear)	180	360	540	720	1260
LUMEN OUTPUT (frosted)	155	310	465	620	1085
WATTAGE	3W	6W	9W	12W	21W
CURRENT	0.13 amps 24V DC	0.25 amps 24V DC	0.38 amps 24V DC	0.5 amps 24V DC	0.88 amps 24V DC
MAX RUN/driver	32 feet	32 feet	32 feet	32 feet	32 feet
VOLTAGE	<b>24V DC ONLY</b>	<b>24V DC ONLY</b>	<b>24V DC ONLY</b>	<b>24V DC ONLY</b>	<b>24V DC ONLY</b>
WIDTH • HEIGHT (XLR)	0.94"W x 0.55"H	0.94"W x 0.55"H	0.94"W x 0.55"H	0.94"W x 0.55"H	0.94"W x 0.55"H
VIEWING ANGLE	90°	90°	90°	90°	90°
WARRANTY (YEARS)	5	5	5	5	5
CONNECTORS	available for all configurations (pg 68)				
POWER SUPPLIES	6 to 300 watt (pg 69 - 72)				
CUSTOMIZING	custom sizing available between 10" and 70" consult LED Lighting Inc.				
NOTE	• lumen output +/- 10%				

#### FEATURES

- aluminium alloy housing
- 6" lead length on either end.
- easy mounting clip & screw installation includes flat (180°) clips, angled (45°) clips available separately (pg 68)
- mounts to wood, steel or metal & most hard smooth surfaces
- damp location
- solid-state, high shock and vibration resistant
- no UV or IR radiation
- occupancy and infrared sensor available (pg 57)

#### OPTIONS

- All Versa Bars are available with a connector on one end and dead end (no connector) on the other end, please consult factory for options and pricing.
- All Versa Bars are available with waterproof connectors, please consult factory for options and pricing.