

**SLR-2120****Under Hood Work Light - Rechargeable**

<b>MARKET APPLICATIONS</b>	Law enforcement, aviation, industrial, automotive and DIY
<b>DESCRIPTION</b>	The SLR-2120 Under Hood Work Light, is purpose built as an all LED, hands-free floodlight for the automotive enthusiast. This rechargeable work light has an adjustable cradle with a pair of spring-loaded, foam-covered grippers that will extend 48"-77" to fit on the underside of virtually any automobile hood. The light bar can then be rotated 360 degrees to place the lighting exactly where it's needed. The 2120 has two brightness modes: High-Brightness (1200 Lumens) and Low-Brightness (650 Lumens). The dual on/off buttons, one located on each of the two handles, operate in tandem with each other. One press of either button turns the light on in High-Brightness Mode, a second press and you're in Low-Brightness Mode and then a third press, turns the light off. The light bar can easily be removed from the cradle. Each of the handles can independently rotate up or down through more than 200 degrees range of motion. The flat surface at the end of each handle can serve as a stand for the light bar. Additionally, there are 3 flush-mounted magnets located in the end of each handle. This allows one or both ends of the light bar to be attached to virtually any flat metal surface. Each handle also has an integrated recessed hook that can swivel 360 degrees making it possible to hang the light bar up. The included AC & DC Power Supplies/Chargers can be used to power the 2120 during use and/or as a way to recharge the unit when it's not in use. Requiring only 6 hours to charge, the SLR-2120 will run for 4.5 hours in High-Brightness Mode, and 8.5 hours when operating in Low-Brightness Mode.
<b>CASE MATERIAL</b>	Engineered Polymer / Steel
<b>DIMENSIONS</b>	Length: 48.5 inches (123 cm) • Width: 4.4 inches (112 mm) • Depth: 6.5 inches (165 mm)
<b>WEIGHT</b>	Weight: 5.5 lbs. (2.5 Kg)
<b>LENS</b>	Polycarbonate
<b>LIGHT SOURCE</b>	SMD LEDs Impervious to shock with a 50,000 + hour lifetime
<b>LIGHT OUTPUT</b>	High-Brightness Floodlight: 1200 lumens • Low-Brightness Floodlight: 650 lumens
<b>ON/OFF</b>	Dual Switches, one on each handle operate in tandem. Half-power, Full-power
<b>RUN-TIME</b>	High-Brightness Floodlight: 4.5 hours • Low-Brightness Floodlight: 8.5 hours
<b>RECHARGE TIME</b>	6 Hours (Run/Charge Design)
<b>BATTERY</b>	Integrated rechargeable Lithium-ion batteries
<b>FEATURES</b>	<ul style="list-style-type: none"><li>• All LED construction</li><li>• Two brightness modes - full-power &amp; half-power</li><li>• Dual spring-loaded grippers with 48"-77" capacity built into the cradle</li><li>• Light bar can be rotated 360 degrees in the cradle or removed all together</li><li>• Light bar handles have 3 magnets each and an integrated hook for added hands-free functionality</li><li>• Light bar handles rotate up and down through more than 200 degrees of range</li><li>• Dual on/off buttons, one located in each handle operate in tandem</li><li>• Integrated rechargeable Lithium-ion battery - no recharge memory effect</li><li>• Includes AC &amp; DC power supplies/chargers</li></ul>
<b>WARRANTY</b>	Limited 1 Year Warranty • Product is warranted to be free from defects in workmanship and materials to the original purchaser for one (1) year from the date of purchase, and includes the LEDs, housing, lenses, electronics, switches, rechargeable batteries and chargers. Disposable non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.

**APPROVALS**