

NEW PRODUCTS

Thermo-Trex® Chemical & Moisture Resistant Ultra-Sleeve™ with Closure

- Continuous Operating Temperature -51°C (-60°F) to 121°C (250°F)



The Thermo-Trex® Chemical & Moisture Resistant Ultra-Sleeve™ with Closure is constructed with a proprietary fabric that is resistant to puncture, tear, abrasion, water & petroleum. The reusable sleeve is intended for use to organize wires and cables and protect against tearing, cut-through and abrasion while offering excellent chemical and moisture resistance.

FEATURES & BENEFITS

- 1. EASY, CUT AND WRAP INSTALLATION** — Reduces downtime and eliminates the need to disassemble existing components to install.
- 2. ABRASION, CHEMICAL AND MOISTURE RESISTANT** — The sleeve is made from tightly woven ballistic Nylon® that sheds surface moisture and has a built-in aggressive, industrial strength hook and loop closure.
- 3. AVAILABLE IN 25' PUT-UPS** — Easy to manage, easy to install.

APPLICATIONS

- Cable Covers
- Cable Tray Protection
- Welding Cable Protection
- Hose Protection
- Anywhere Rubbing or Vibration Occurs
- Water, Grease & Hydraulic Oils Protection

CHEMICAL RESISTANCE CHART (1= No Effect 2= Little Effect 3= Affected 4= More Affected 5= Severely Affected)

Aromatic Solvents	1	De-Icing Fluid (MIL-A-8243)	1	Aliphatic Solvents	1	Strong Acids	1
Chlorinated Solvents	1	Strong Oxidants	1	Weak Bases	1	Esters/Keytones	1
Strong Bases	1	UV Light	1	Salt Water (O-S-1926)	1	Petroleum	1
Hydraulic Fluid (MIL-H-5606)	1	Fungus (ASTM G-21)	1	Lubricating Oil (MIL-A-8243)	1	Salts	1

ORDERING INFORMATION (Call for pricing & availability)

PART NO.	NOMINAL SIZE (IN)	WALL THICKNESS (IN)	HOOK & LOOP WIDTH (IN)	STANDARD SPOOL PUT-UPS (FT)		AVAILABLE COLORS	WT. (LBS) PER 100'
				BULK SPOOL	SHOP SPOOL		
CMRW138	1.375	0.05	1.250	75	25	Black	19.6
CMRW300	3.00	0.05	1.250	75	25	Black	21.6



TPC WIRE & CABLE CORP.
EXPECT HIGH PERFORMANCE®

TPC WIRE & CABLE CORP. HEADQUARTERS 9600 VALLEY VIEW RD, MACEDONIA, OHIO 44056
USA 800-521-7935 • FAX 866-528-2930 • CANADA 800-545-0122 • MEXICO 001-877-283-1696
CHILE 1230-020-0229 • COLOMBIA 0-1-800-915-7519 • PERU 0800-54863 • WWW.TPCWIRE.COM

WARRANTY AND DISCLAIMER: Seller makes no warranties, express or implied, with respect to this product, and seller disclaims any implied warranties of merchantability or fitness for any particular purpose. Further, seller will not be responsible for any consequential, incidental or indirect damages (including, but not limited to, any loss of profit) from any cause whatsoever.

TPC1374 (02/15) ©Copyright 2015 by TPC Wire & Cable Corp. All rights reserved. No portion of this publication, whether in whole or in part, can be reproduced without the express written consent of TPC Wire & Cable Corp.

