

PC 5070

7" HD 1024 x 600 Multi-Touch N2807 Fanless Embedded PC IP65 Rated Flat Front Bezel



» Features

- » IP65 rated flat front bezel
- » 7 inch 1024 x 600 LED backlight monitor
- » Projected Capacitive Multi-touch screen monitor
- » 500-nits high brightness LCD panel
- » Celeron N2807 Dual Core 1.58GHz embedded system
- » -20°C to 50°C wide range working temperature
- » 9~30V DC power input with external AC power adapter

» Specifications

Material:

IP65 rated rugged enclosure

LCD Panel:

Size: 7"

Max. Resolution: 1024 x 600

Brightness: 500nits

Contrast Ratio: 700:1

Viewing Angel (H/V): 150° x 145°

Pixel Pitch (mm): 0.05(H) x 0.15(V)

System:

CPU: Celeron N2807 Dual Core 1.58GHz CPU

Memory: 2GB DDR3 SO-DIMM

Storage: 30GB mSATA SSD

Touch Screen:

Projected capacitive multi- touch screen monitor

USB port

Audio:

1 x AMP 2W internal speaker

Wireless Communication:

Built-in IEEE 802.11a/b/g/n/ac 1T1R module

Connectors:

2 x COM (RS-232)

2 x USB 3.0

2 x Gigabit Ethernet ports (RJ-45)

1 x power switch

1 x reset button

1 x AT/ATX switch

1 x Audio (Line-out)

1 x 9~30V lockable DC jack

Power Supply:

9~30V DC power input with external AC power adapter

Mounting:

Wall, Panel, Stand, Rackmount, VESA (75*75mm)

Color:

Black

Weight:

1.61lbs

Dimension:

7.52"(W) x 1.71"(D) x 5.01"(H)

Certification:

CE, FCC

Environmental:

Operating: -20°C to 50°C (14°F to 122°F)

Storage: -20°C to 60°C (14°F to 122°F)

Relative humidity: 10% to 95%, non-condensing

» Ordering Guide

PC5070:

7 inch 1024 x 600 500-nit high brightness industrial fanless Panel PC with projected capacitive multi-touch screen, Celeron N2807 Dual Core 1.58GHz CPU, 2GB DDR3 SODIMM memory, 30GB mSATA SSD, IP65 rated flat front bezel, black color.