

## XPP-5454G

## Intrinsically Safe Multi-Function Dual-Light™ Headlamp

MARKET APPLICATIONS

Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

DESCRIPTION

LIGHT OUTPUT

This non-rechargeable multi-function Dual-Light™ headlamp is cETLus, ATEX and IECEx listed Intrinsically Safe. This headlamp features a multi-position tilt head design and includes an elastic head strap with a non-slip lining and a heavy-duty rubber head strap for use on a hard hat. The dual top mounted switches provide user-selectable high or low-brightness spotlight, high or low-brightness floodlight operation and our exclusive Dual-Light design…the ability to turn on both the spotlight and the floodlight at the same time for maximum user safety and lighting versatility. Power comes from 3 AAA premium batteries (included).

**CASE MATERIAL** Engineered Polymer - Green

**DIMENSIONS** Width: 2.6 inches (66 mm) • Height: 2.1 inches (53 mm) • Depth: 1.8 inches (46 mm)

**WEIGHT** Weight: 3.3 oz. (94 g) with batteries installed

LIGHT SOURCE

Unbreakable polycarbonate with scratch resistant coating
CREE® LED Impervious to shock with a 50,000 hour lifetime

High-Brightness Spotlight: 100 lumens • Low-Brightness Spotlight: 60 lumens • High-Brightness Floodlight: 90 lumens

• Low-Brightness Floodlight: 50 lumens • Dual-Light: 115 lumens

**ON/OFF** Dual Switches. High/Low Spotlight, High/Low Floodlight, Dual-Light

RUN-TIME High-Brightness Spotlight: 5 hours • Low-Brightness Spotlight: 13.5 hours • High-Brightness Floodlight: 4.25 hours •

Low-Brightness Floodlight: 13.75 hours • Dual-Light: 3.5 hours

BATTERY 3 Alkaline AAA batteries (included)

• cETLus, ATEX and IECEx listed Intrinsically Safe


- CREE® LED technology 50,000 + hours LED life
- High/low-brightness spotlight, high/low-brightness floodlight
   & Dual-Light™
- · Focused spotlight beam for distance illumination
- · Wide unfocused floodlight beam for close-up illumination
- · Engineered polymer housing
- Dual switches located on top of light
- · Adjustable ratchet tilt head
- · Non-slip elastic head strap
- · Heavy-duty rubber strap for hard hat applications
- Waterproof
- · Impact & chemical resistant
- Powered by 3 premium AAA alkaline batteries (included)

| FL1 STANDARD | HIGH          | LOW          |
|--------------|---------------|--------------|
| 31/2         | 115<br>LUMENS | 60<br>LUMENS |
| (            | 5h            | 16h 15min    |
|              | 82m           | 60m          |
|              | 1668cd        | 882cd        |
| 2m<br>1m     |               |              |

WARRANTY

Limited Lifetime Warranty • Includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.

## **APPROVALS**



## Nightstick 5454 Headlamp

Intertek

ID 4008947 INTRINSICALLY SAFE SECURITE INTRINSEQUE

CLASS | DIV 1 GRPS A-D T3 CLASS | I & III GRPS E-G T135C CLASS | ZONE 0 AEx ia IIC T3 Ga CLASS | ZONE 0 Ex ia IIC T3 Ga © II 1 G Ex ia IIC T3 Ga

Ex ia IIC T3 Ga
Intertek ITS 13 ATEX27928X
IECEx ETL 13.0045X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell AAA Alkaline

Conforms to:

ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11 ANSI/ISA 60079-26 Certified to: CAN/CSA STD C22.2 No 157 CAN/CSA STD C22.2 No 60079-0 CAN/CSA STD C22.2 No 60079-11 CSA STD C22.2 No 25

Designed in USA, manufactured in China at a ISO-9001 certified Bayco facility.

PDS\_XPP-5454G\_150420\_A