

QUALITY TOOLS THAT GO TO WORK WITH YOU®



HUMM•VAC® VACUUM PUMPS

3 WAY INTAKE FITTING
WITH TETHERED CAPS
AND CHECK VALVE

NON-SLIP
RUBBER HAND GRIP

SLANT BACK
CENTER BALANCED
HANDLE

GAS BALLAST

OIL FILL
PORT AND
EXHAUST DOME

DUAL
VOLTAGE
POWER BOX

HEAT
DISPERSING
RESERVOIR
FINS

POWERFUL
LOW DECIBEL
FAN COOLED
MOTOR

LARGE
SIGHT GLASS
FOR EASY OIL
MONITORING

HEAT
DISPERSING
MOTOR
FINS

BEVELED RESERVOIR
PAN FOR COMPLETE
OIL DRAINAGE

SURE-GRIP
RUBBER
FOOT PADS

LOW PROFILE
EASY ACCESS
OIL DRAIN

WIDE,
STABLE
FOOT
PRINT



UNIWELD®
PRODUCTS, INC.
FT. LAUDERDALE
FL 33312 U.S.A.
www.uniweld.com



HUMM•VAC[®] VACUUM PUMPS

The Uniweld exclusive HUMM•VAC[®] Pumps remove moisture and dehydrate a system quickly and efficiently. The all-metal, heavy duty chassis; powerful, quiet running dual voltage motor; lighter weight and ergonomically designed features make these pumps the #1 choice to go to work with you.



Pump Specifications

	HVP6	HVP8	HVP12
Free Air Displacement	6.0 CFM, 170 liter/min.	8.0 CFM, 226 liter/min.	12.0 CFM, 340 liter/min.
Number of Stages	2-Stage Rotary Vane	2-Stage Rotary Vane	2-Stage Rotary Vane
Factory Micron Rating	15 Microns	15 Microns	15 Microns
Intake Fittings	1/4", 3/8" Male Flare and 1/2" Acme	1/4", 3/8" and 1/2" Male Flare	1/4", 3/8" and 1/2" Male Flare
Thermal Overload Protection	1/2HP	3/4HP	3/4HP
Voltage	110/220V - 50/60Hz	110/220V - 50/60Hz	110/220V - 50/60Hz
Oil Capacity	1 Quart (946 ml)	31.3 Ounces (925 ml)	27.7 Ounces (820 ml)
Power Cord	72" (1.83m)	72" (1.83m)	72" (1.83m)
Dimensions	14.50" x 6.875" x 10.75" 36.83 cm x 17.46 cm x 27.30 cm	15.0" x 6.875" x 10.75" 38.1 cm x 17.46 cm x 27.3 cm	15.0" x 6.875" x 10.75" 38.1 cm x 17.46 cm x 27.3 cm
Weight	26 Lbs. (11.80 kg)	34 Lbs. (15.42 kg)	35 Lbs. (15.88 kg)
Shipping Weight	30 Lbs. (13.60 kg)	38 Lbs. (17.24 kg)	39 Lbs. (17.70 kg)
Color	Yellow	Red	Black

USE ONLY
PREMIUM UNIWELD
VACUUM PUMP OIL

42005 Quart
(.946 liter) 12 per case
42006 Gallon
(3.78 liters) 6 per case



UNIWELD[®] PRODUCTS, INC.
2850 Ravenswood Road, Fort Lauderdale, FL 33312
Customer Service: 800.323.2111 • 954.584.2000 • Fax: 954.587.0109
www.uniweld.com • info@uniweld.com

U.S. PATENT #D0518068

Scan
With
Smart
Phone

