

SPECIFICATION SHEET

LED PUCK LIGHT



Job Name	
Customer	
Item Number	SRP2-04-AC-2700-B-1
Quantity	

LED Lighting Inc.'s surface/recess mount puck is dimmable and features an ultra slim design.

Recommended applications include: show cases, shelf lighting, trade show booths, under cabinet lighting, display cases, retail stores, bookcase lighting, closets, flush ceiling mounting and general illumination.

SPECIFICATIONS

COLOR TEMPERATURE (CCT)	2700К
SHAPE	ROUND
CASE COLOR	BLACK
LENS	FROSTED
DIAMETER	2.75″
HEIGHT	ן"
LEAD LENGTH	6″
LUMEN OUTPUT +/-10%	220
VOLTAGE	120V AC
POWER CONSUMPTION	4W
VIEWING ANGLE	CENTER SECTION SWIVELS FOR DIRECTIONAL LIGHT CONTROL
CRI	90+
MOUNTING	SCREWS (INCLUDED)
ENVIRONMENT	INDOOR
CERTIFICATIONS	() () ()
WARRANTY	5 YEARS

FEATURES

LAIUN		
	One 6" Lead wire	
FEATURES	Zinc alloy light housing with aluminum heat sink.	
	Line voltage, without the need for a driver	
	Easily mounts with screws.	
	Mounts to steel, wood or metal & most hard surfaces.	
	Dimmable with most standard wall dimmers	
	Contains a Triac dimmable driver, on/off switch included	
	Polycarbonate lens	
	Link up to 20 pucks to a single power supply	
	Requires a junction box for operation, sold separately.	
2 3/4"		
1 ¹¹ /16 ¹¹		



Phone: (847) 412-4880 Fax: (847) 412-4881 15/16"