



EC750GTAA Ecologic UPS

Offering advanced energy-saving battery backup and protection against power surges and interruptions.

The CyberPower Federal Trade Agreements Act (TAA) compliant Ecologic EC750GTAA UPS safeguards PCs and other electronics from blackouts, brownouts, surges, spikes, sags, and other power abnormalities. Its composite integrated circuitry offers reliable surge protection and battery backup during power interruptions. This UPS utilizes GreenPower UPS™ high efficiency design to reduce power consumption and is an ENERGY STAR® qualified battery backup.

The CyberPower EC750GTAA has three surge protected ECO outlets. When ECO mode is on and the battery backup detects that your computer is off or in Sleep mode, computer peripherals connected to the ECO outlets will be turned off (USB connection required). This reduces unneeded power usage and provides greater energy savings.

A three-year warranty ensures that this UPS has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$100,000 Connected Equipment Guarantee.

Typical Applications

- Desktop Computers
- Workstations
- Personal Electronics
- Home Networking/VoIP

Features

- 750VA / 450W
- Standby Topology
- Selectable ECO Technology
- GreenPower UPS™ Technology
- ENERGY STAR® Qualified
- Full-time Surge Protection and Battery Backup
- Compact Form Factor
- 12 Outlets/USB Port/RJ11 Protection
- PowerPanel® Personal Edition
- 3-Year Warranty

EC750GTAA Ecologic UPS

Offering advanced energy-saving battery backup and protection against power surges and interruptions.

SPECIFICATIONS	
Model Number	EC750GTAA
GENERAL	
UPS Topology	Standby
Energy Saving	GreenPower UPS™ High Efficiency
ENERGY STAR® Qualified	Yes
INPUT	
Voltage	96Vac - 140Vac
Frequency	47Hz - 63Hz
Plug Type	NEMA 5-15P
Plug Style	Right Angle - 45° Offset
Cord Length	5'
OUTPUT	
VA	750
Watts	450
On Battery Voltage	120Vac ±5%
On Battery Frequency	50/60Hz ±1% (auto-sensing)
On Battery Waveform	Simulated Sine Wave
Outlets - Total	12
Outlet Type	NEMA 5-15R
Outlets - Eco Controlled	3
Outlets - Battery & Surge Protected	6
Outlets - Surge-Only Protected	6
Outlets - Widely Spaced	4
Overload Protection	Internal circuitry limiting / circuit breaker
Transfer Time	4ms
BATTERY	
Runtimes	8.8 min. (225W), 1.7 min. (450W)
Runtime at Half Load (min)	8
Runtime at Full Load (min)	1
Battery Type	Sealed Lead-Acid
Typical Recharge Time	8 Hours
SURGE PROTECTION & FILTERING	
Surge Suppression	526 Joules
Phone Protection RJ11	1-in/1-out
EMI/RFI Filtration	Yes

SPECIFICATIONS (continued)	
Model Number	EC750GTAA
MANAGEMENT & COMMUNICATIONS	
HID Compliant USB Port	Yes
Management Cable	USB Cable
LED Indicators	Power On, ECO on/off
Audible Alarms	Battery Mode, Battery Low, Overload
Software	PowerPanel® Personal Edition
PHYSICAL	
Form Factor	Compact
Dimensions (WxHxD) (in)	12.2 x 3.1 x 7.0
Dimensions (WxHxD) (mm)	309.9 x 78.7 x 177.8
Weight	7.7 lb (3.5 kg)
ENVIRONMENTAL	
Operating Temperature	+32°F to +104°F / 0°C to +40°C
Operating Humidity	0% - 95% non-condensing
Operating Elevation	0-10000 ft (0-3000 m)
Storage Temperature	+5°F to +113°F / -15°C to +45°C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 ft (0-15000 m)
CERTIFICATIONS	
Safety	UL1778, cUL 107.3, FCC DOC Class B
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$100,000