



IPC R1x Mini Rugged PC



Networking	<ul style="list-style-type: none"> • 1x Intel 82579LM Gigabit LAN supports iAMT 8.0 • 1x Intel 82574L Gigabit LAN 	Shock Protection Standards	<ul style="list-style-type: none"> • IEC60068-2-27
CPU Support	<ul style="list-style-type: none"> • Intel 3rd Generation Core i5/i7 	Wall Mount	<ul style="list-style-type: none"> • Custom mounting bracket
I/O Ports	<ul style="list-style-type: none"> • 4x USB 3.0 Ports • 2x USB 2.0 Ports • 3x RS232 • 1x RS232/422/485 • 16x Isolated DC In • 16x Isolated DC Out 	Display Outputs	<ul style="list-style-type: none"> • VGA, DVI-D: 1920 x 1200 • Display Port 1: Up to 2560 x 1600 • Display Port 2: Up to 1920 x 1200
Chipset	<ul style="list-style-type: none"> • Intel QM77 	Expansion Slots	<ul style="list-style-type: none"> • 2x Mini PCI-e (1x Half-sized and 1x Full-sized) • 2x PCI-e (One x16 Slot and one x4 Slot)
Memory	<ul style="list-style-type: none"> • Up to 16GB DDR3 	HDD Support	<ul style="list-style-type: none"> • 2x 2.5" SATA HDD/SSD
Operating System	<ul style="list-style-type: none"> • Windows 10, 8, Windows 7, Linux 	Weight	<ul style="list-style-type: none"> • 7.7 lbs
Video & Graphics	<ul style="list-style-type: none"> • Intel GMA HD 4000 	Certifications	<ul style="list-style-type: none"> • CE, FCC, RoHS, EN50155 & EN50121-3-2
Dimensions	<ul style="list-style-type: none"> • 9.9" x 5.4" x 8.3" (L, W, H) 	Colors	<ul style="list-style-type: none"> • Aluminum and Green (Two-Tone)
Audio	<ul style="list-style-type: none"> • Realtek ALC892, 5.1 Channel HD Audio • 1x Mic-in • 1x Line-out 	Power Supply	<ul style="list-style-type: none"> • 120W 9~36V wide range input support
Environment	<ul style="list-style-type: none"> • Operating Temperature: -25°C ~ 70°C • Storage Temperature: -40°C ~ 85°C 	Humidity	<ul style="list-style-type: none"> • 10% ~ 95% (non-condensing) • Relative Humidity: 95% at 70°C
IEC Vibration Standards	<ul style="list-style-type: none"> • IEC68-2-64 	Others	<ul style="list-style-type: none"> • TPM 1.0, LPC Interface • Watchdog Timer - Reset : 1 to 255 sec./min. per step • Wake on LAN, PXE supported • Auto Monitoring of temperature & voltages & cut off circuit.