

Linkus

Yeastar Mobile Client



Linkus is a VoIP Mobile Client coordinated with Yeastar S-Series VoIP PBX that makes your Android or iOS mobile phone an office extension and links you and your colleagues and customers anywhere anytime. Make and receive calls through corporate phone network to slash call costs and enhance efficiency with consistent in-office experience.



Key Capabilities

- Make and receive enterprise VoIP calls over your Wi-Fi or mobile data networks to cut mobile voice charges
- One number reach to conceal your mobile phone number and ensure unified corporate identity
- Set up flexible ring strategy for Linkus and the desktop phone
- Select different outbound routes for different destinations (local/long-distance/international, etc.)
- Corporate directory integration with lookup and call availability indicator (available/unavailable/busy)
- Configurable PBX features including Call Transfer, Call Forwarding, Call Waiting, DND
- Support CallKit to so you could have the standard call control UI of iOS and better call quality

Main Features

Call Forwarding
CallKit (iOS 10)
Call History
Call Route Selection
Call Transfer

Call Waiting
Contact Management
Corporate Directory
Do Not Disturb

Extension Status
Hold & Resume
Native Contacts Integration
One Touch Recording

Outbound Route Selection
PUSH Notification (iOS)
Ring Strategy Selection
Speed Dial/Favorite
Voicemail



Specifications

iOS Requirement: iOS 8.0 or higher

Android Requirement: Android 4.4 or higher

PBX Requirement: S-Series VoIP PBX firmware version 30.2.0.27 or higher


Network: 2G/3G/4G or Wi-Fi

Protocol: SIP FRC3261

Codec: iLBC

Network Protocol: TCP/IP/UDP, RTP/SRTP/RTCP, HTTP/HTTPS

DTMF: Inband, RFC4733 (RFC2833), Info



About Yeastar

Yeastar specializes in the developing and manufacturing of IP-PBX and VoIP gateways, and is committed to the distribution of new generation technology products in the field of enterprise communications.

Tel: +86-592-5503301

E-mail: sales@yeastar.com

Web: www.yeastar.com

