

HURRICANE DISASTER RELIEF

20% OFF all devices except wall plates from now until 12/31/17

6WAD3FAD766L_Vd

- Dimmable LED, CFL, and Incandescent control
- Single Pole/Three-way
- Dimming control fades up and down smoothly
- 700 watts Incandescent
- 150 watts LED
- 120VAC, 60Hz
- White



51300-W

\$7.- &

DECORATOR SWITCHES

- Smooth, quiet paddle action
- 15 AMP Push-in and side wired 120-277VAC
- Single-pole
- White, Ivory, Almond, Light Almond, Black, Brown



91150



\$5*

DECORATOR SWITCHES

- Smooth, quiet paddle action
- 15 AMP Push-in and side wired 120-277VAC
- Three-way
- White, Ivory, Almond, Light Almond, Black, Brown



93150



\$5, (

DECORATOR SWITCHES

- Smooth, quiet paddle action
- 15 AMP Push-in and side wired 120-277VAC
- Four-way
- White, Ivory, Almond, Light Almond, Black, Brown



94150



\$8*5

675AD3FAD766L_Vd

- Residential Grade
- 15A / 125V
- Push-in and Side Wired
- Self-grounding
- White, Ivory, Almond, Light Almond, Black, Brown



61501-TR-W



\$5, (

675AD3FAD STRAIGHT BLADE D757BF35>7

- Residential Grade
- 15A / 125V
- Push-in and Side Wired
- Self-grounding
- White, Ivory, Almond, Light Almond, Black, Brown



61501-W



\$5(

DUPLEX F3? B7D7E;EF3@F D757BF35>7

- Residential Grade
- 3 Wire Grounding, 15A 125V
- Push-in and Side Wired
- Self-grounding
- White, Ivory, Almond, Light Almond, Black, Brown



61580-TR



\$5)

DUPLEX STRAIGHT BLADE D757BF35>7

- Residential Grade
- 3 Wire Grounding, 15A 125V
- Push-in and Side Wired
- Self-grounding
- White, Ivory, Almond, Light Almond, Black, Brown



61580-W



\$5&(

TOGGLE SWITCHES

- 15 AMP 120/277 VAC
- Push-In and Side Wired
- Single-pole
- White, Ivory, Light Almond



88115-W



\$5' &

TOGGLE SWITCHES

- 15 AMP 120/277 VAC
- Push-In and Side Wired
- Three-Way
- White, Ivory, Light Almond



83150-W



\$5(

TOGGLE SWITCHES

- 20 AMP 120/277 VAC
- Push-In and Side Wired
- Single-pole
- White, Ivory



81200-W



\$5- &

INDUSTRIAL GRADE RECEPTACLES

- 3 Pole
- 30 Amps
- 125/250 V
- 4 Wire Grounding
- NEMA 14-30



66600



\$8' %

INDUSTRIAL GRADE RECEPTACLES

- 3 Pole
- 50 Amps
- 125/250 V
- 4 Wire Grounding
- NEMA 14-50



66500



\$8' %

INTERCHANGEABLE COVER USB RECEPTACLE

- Interchangeable face cover
- Includes: light almond and black cover
- Tamper Resistant
- Voltage: 125VAC, 60Hz
- Max load: 15A
- Output: 5VDC 4.8A
- White



61501-TR2USB-CC



\$8&&

OCCUPANCY/VACANCY SENSOR SWITCH

- Single pole, OCC/VAC sensor switch
- Neutral wire required
- Incandescent: 500W@120VAC
- Fluorescent: 500VA@120VAC
- LED: 150W
- Motor: 1/8HP@120VAC
- White, Ivory, Almond, Light Almond



HMOS



\$, .5*

DUAL-TECH HUMIDITY/PIR MOTION SENSOR

- Single Pole, 120VAC 60Hz
- 1/4th HP (3-AMP) fan
- Time Delay: 10, 20, and 30 minutes
- Humidity Set Point: 45%-80%
- Interchangeable face cover
- Separate load required for light/fan
- Neutral wire required
- White



DWHOS



\$81.00

Enerlites Inc.

1781 McGaw Ave Irvine, CA 92614 Tel: 949 756 0536 Fax: 949 756 0528
www.enerlites.com sales@enerlites.com

Disclaimer:
* Price valid to customers in Texas and Florida only