



Rubber Sheet Roll

Technical Data Sheet

COLOR	BLUE/GREY/RED/GREEN
SURFACE	SEMI-SMOOTH
STATIC LOAD LIMIT	(ASTM F970) 1,000 PSI
TENSILE	200 LBS / SQ INCH MIN
DUROMETER	75A NOMINAL
ELONGATION AT BREAK	75 % MIN
FIRE RATED	NO
UV RATED	GOOD
CHEMICAL RESISTENT	GOOD
COMPOSITION	EPDM / RECYLCED

ADHESIVE DATA

THICKNESS	5 MILS
SURFACE	LIQUID
TEMPERATURE	150° F
COMPOSITION	POLYURETHANE

Description

rubber Sport flooring also known as gym flooring, has a very strong compression set to prevent tearing and degradation. This rubber sport flooring is slip resistant in wet or dry environments making it a good selection for work-out areas.

Rubber Sheet Roll Shippensburg, PA 17257

Phone: 866.832.6006

info@rubbersheetroll.com www.rubbersheetroll.com

All values given are averages based on test samples and the data given is based on what we have determined to be reliable. As results cannot be predicted or guaranteed for any specific set of conditions, each user should make their own determination of these products suitability for their particular application. **Viton®** is a registered trademark of DuPont Performance Elastomers.

SPORT FLOORING

SPORT FLOORING